



PROLITE E2473HDS

The ProLite E2473HDS LED-backlit monitor, finished in the latest glossy-black, is a full high definition 24" display that features all the benefits this technology affords. The high specifications of the monitor include the 5,000,000:1 ACR, triple input connectivity (D-Sub, DVI-D, 2 x HDMI) and fast 2ms response for excellent sharpness in high definition video. VESA mount compatibility along with one HDMI input and headphone connector on the side of the cabinet ensures great comfort of usage.

DISPLAY CHARACTERISTICS

| | |
|---------------------------|--|
| Diagonal | 23.6" |
| Panel | LED-Backlit |
| Display area h x w | 293.2 x 521.3 mm; 11.54" x 20.51" |
| Response time | 2 ms |
| Contrast | 1000 : 1 typical |
| Contrast | 5 000 000 : 1 ACR |
| Brightness | 300 cd/m ² typical |
| Viewing zone | horizontal/vertical: 170°/ 160°; right/left: 85°/ 85°; up/down: 80°/ 80° |
| Display colour | 16.7 million |
| Pixel pitch h x v | 0.2715 x 0.2715 mm |
| Native resolution | Full HD 1080p, 1920 x 1080 (2.1 megapixel) |
| Horizontal sync | 24 - 80 KHz |
| Vertical sync | 55 - 75 Hz |
| Synchronization | Separate sync |
| Aspect ratio | 16 : 9 |

INTERFACES & CONNECTORS

| | |
|--------------------------------|---------------------|
| Analog input connector | D-Sub |
| Digital input connector | DVI-D, 2 x HDMI |
| HDCP | yes |
| Output connector | headphone connector |

SPECIAL FEATURES

| | |
|--------------------------|---|
| Apple - Mac | All iiyama monitors are compatible with Apple-Macintosh computers. |
| Plug & Play | VESA DDC2B™ |
| Controls | Via OSD in 8 languages (EN, DE, FR, ES, IT, FIN, Chinese, JP) and 5 front controls (Power, Select/ Input Select, Scroll up/ Audio , Scroll down/ i-Style Colour, Menu) |
| User controls | auto adjust, contrast/brightness (contrast, brightness, ACR, ECO, OD), input select, audio adjust (volume, mute, HDMI audio), colour adjust, information, manual image adjust (clock, H/V position, phase, sharpness, video mode adjust), setup menu (language, OSD position, OSD time out, OSD background, LED), memory recall |
| Speakers | 2 x 2 W (Stereo) |
| Anti-theft-device | Kensington-lock™ prepared |
| Ergonomics | TCO5.1, CE, TUV-Bauart, VCCI-B, PSE |
| Tilt angle | 20° up; 0° down |
| VESA mounting | 100 mm |
| Colour | Black |

ACCESSORIES

| | |
|-----------------------------|--|
| Driver | Windows 95 / 98 / 2000 / ME / XP / Vista / 7 |
| Included accessories | power cable, D-Sub cable, DVI-D cable, audio cable, stand, cable holder, quick start guide, safety guide |

POWER MANAGEMENT

| | |
|--------------------------|--------------------|
| Power supply | AC100–240V 50/60Hz |
| Power Supply Unit | internal |

| | |
|--------------------|---|
| Power usage | 24 W typical; max. 1 W in Power management mode |
|--------------------|---|

| | |
|-------------------------|-------------------------|
| Power management | VESA DPMS, ENERGY STAR® |
|-------------------------|-------------------------|

DIMENSIONS & WEIGHT

| | |
|-----------------------------|----------------------|
| Dimensions w x h x d | 556 x 418 x 218.5 mm |
|-----------------------------|----------------------|

| | |
|---------------|--------|
| Weight | 4.4 kg |
|---------------|--------|

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.