



## Network Camera Outdoor Enclosures

### Outdoor Protection for Surveillance Cameras

- Water Resistance/Dust-Proof Protection
- Heater/Blower for Protection Against Heat/Cold Temperature
- Built-in Power Supply for Easy Cable Management
- Angle-Adjustable Mounting Brackets
- Vertical or Horizontal Installation

The D-Link SecuriCam Network camera outdoor enclosures provide a cost-effective solution for protecting your D-Link Network Camera from the rigors of outdoor use. The fixed-type enclosures include heavy-duty, angle-adjustable mounting brackets that can be used to secure the camera on a vertical or horizontal surface. These enclosures maximize the full potential of your D-Link Network cameras to secure and protect your home and business.

#### DCS-45 IP66 Certified

The DCS-45 is IP66 certified for water resistance and dust proof operation. The housing is complete with an adjustable semi-cable managed bracket.

**Supported Devices**

- DCS-3220
- DCS-3110
- DCS-3410

**Dimensions**

390(L) x 127(W) x 124(H) mm (15.4 x 5 x 4.9inches)

**Weight**

3.00kg (6.61lb)

**Material**

Aluminum Housing

**Color**

White

#### DCS-50 IP66 Certified With Built-In Power Supply

The DCS-50 is IP66 certified for water resistance and dust-proof operation. This model includes a built-in power supply for easy cable management.

**Supported Devices**

- DCS-3220
- DCS-3110
- DCS-3410

**Power Supply**

90 to 264V AC Input, 12V DC, 3A Output

**Dimensions**

390 (L) x 127 (W) x 124 (H) mm (15.4 x 5 x 4.9 inches)

**Weight**

3.05 kg (6.72 lb)

**Material**

Aluminum Housing

**Color**

White

**Operation Temperature**

-20° to 45° C (-4° to 113° F) (Enclosure)

**Humidity**

5% to 95% RH non-condensing (Enclosure)

## **DCS-60** IP44 Certified With Built-In Power Supply, Heater And Blower

The DCS-60 is IP44 certified for water resistance and dust-proof operation. This model includes a heater and blower for a wider range of temperature-sensitive environments. The built-in power supply simplifies the installation procedure.



### **Supported Devices**

- DCS-3220   ▪ DCS-3415
- DCS-3410   ▪ DCS-3110

### **Power Supply**

90 to 264V 264V AC Input, 12V DC, 3A Output

### **Heater**

On at 18°C (64°F), Off at 28°C (82°F)

### **Blower**

On at 35°C (95°F), Off at 25°C (77°F)

### **Dimensions**

450 (L) x 135 (W) x 140 mm (H)  
(17.7 x 5.3 x 5.5 inches)

### **Weight**

4.3 kg (9.47 lb)

### **Material**

Aluminum Housing

### **Color**

White

### **Operation Temperature**

-20°C to 45°C (-4°F to 113°F) (Enclosure)

### **Humidity**

5% to 95% RH non-condensing (Enclosure)

## **DCS-70** Dome Type, IP66 Certified With Built-In Power Supply, Heater And Blower

The DCS-70 is a dome-type enclosure and is designed for use with D-Link's motorized pan and tilt cameras. This IP66 certified enclosure protects your camera against dust and heavy jets of water. Camera installation is simplified with the built-in power supply, while the heater and blower keeps your camera in proper operating temperatures.



### **Supported Devices**

- DCS-5300   ▪ DCS-5610
- DCS-6620

### **Power Supply**

100 to 240V AC Input, 12V DC, 3A Output

### **Heater**

On at 0°C (32°F), Off at 10°C (50°F)

### **Blower**

On at 40°C (104°F), Off at 30°C (86°F)

### **Dimensions**

225 (H) x 218 (D) mm (8.86 x 8.58 inches)

### **Weight**

3.4 kg (7.27 lb)

### **Material**

Aluminum Housing with Smoked Acrylic Cover

### **Color**

Beige

### **Operation Temperature**

-20°C to 50°C (-4°F to 122°F) (Enclosure)

### **Humidity**

0% to 95% RH non-condensing (Enclosure)