



Specifications

© 2013 Dell Inc.

Trademarks used in this text: Dell™, the DELL logo, and Inspiron™ are trademarks of Dell Inc. Intel® is a registered trademark and Core™ is a trademark of Intel Corporation in the U.S. and other countries. Bluetooth® is a registered trademark owned by Bluetooth SIG, Inc. and is used by Dell under license.

2013 - 10 Rev. A00

Regulatory model: P24E | Type: P24E001

Computer model: Inspiron 7737

Dimensions and Weight:

Height:

Non-touch	1 in (25.40 mm)
-----------	-----------------

Touch	1.10 in (27.70 mm)
-------	--------------------

Width	16.24 in (412.40 mm)
-------	----------------------

Depth	10.61 in (269.40 mm)
-------	----------------------

Minimum weight:

Non-touch	6.59 lb (2.99 kg)
-----------	-------------------

Touch	7.25 lb (3.29 kg)
-------	-------------------

NOTE: The weight of your laptop varies depending on the configuration ordered and the manufacturing variability

System Information

Computer model	Inspiron 7737
----------------	---------------

Processor	<ul style="list-style-type: none">• Intel Core i3 (4th generation)• Intel Core i5 (4th generation)• Intel Core i7 (4th generation)
-----------	---

L1 cache	32 KB
----------	-------

L2 cache	256 KB
----------	--------

L3 cache	Up to 4 MB
----------	------------

Chipset	Integrated in processor
---------	-------------------------

Memory

Connectors	Two SODIMM connectors
------------	-----------------------

Type	DDR3L
------	-------

Speed	Up to 1600 MHz
-------	----------------

Configurations supported	6 GB, 8 GB, and 16 GB
--------------------------	-----------------------

Ports and Connectors

External:

Network	One RJ45 port
USB	<ul style="list-style-type: none">• Three USB 3.0 ports• One USB 3.0 port with PowerShare
HDMI port	One HDMI port
Audio	One headset port

Internal:

Mini-card	One half mini-card slot for Wi-Fi and Bluetooth combo
-----------	---

Communications

Network adapter	RJ45 port
Wireless	<ul style="list-style-type: none">• Wi-Fi 802.11 b/g/n• Bluetooth 4.0• Wireless Display (optional)

Video

Controller:

Integrated	Intel HD Graphics 4400
Discrete	nVidia GeForce GT 750M

Memory:

Integrated Memory	Shared system memory
Discrete Memory	2 GB GDDR5

Audio

Controller	ALC3223
Speaker	Two- 2 Watt
Internal microphone	Digital-array microphones
Volume controls	Program menus and keyboard shortcut keys

Storage

Interface	SATA 6 Gbps
Hard drive	One 2.5-inch drive (supports Intel Smart Response Technology)
Optical drive	One 9.5 mm DVD+/-RW

Media-card reader

Type	One 8-in-1 slot
Cards supported	<ul style="list-style-type: none">• SD card• SD High-Capacity (SDHC) card• SD Extended-Capacity (SDXC) card with Ultra High Speed (UHS)• Memory Stick (MS)• Memory Stick Pro• Memory Stick XC (MSXC)• MultiMedia Card (MMC)• MultiMedia Card plus (MMC+)

Display

Type:	
Non-touch	17.3-inch HD
Touch	<ul style="list-style-type: none">• 17.3-inch HD• 17.3-inch full HD
Resolution (maximum):	
HD	1600 x 900
Full HD	1920 x 1080
Dimensions:	
Height	8.46 in (214.81 mm)
Width	15.04 in (381.89 mm)
Diagonal	17.30 in (439.42 mm)
Refresh rate	60 Hz
Operating angle	0 degrees (closed) to 135 degrees
Pixel pitch	0.239 mm
Controls	Brightness can be controlled using shortcut keys.

Keyboard

Type	Backlit keyboard with numeric keypad
------	--------------------------------------

Camera

Camera resolution:

Still image	0.92 megapixel
Video (maximum)	1280 x 720 (HD) at 30 fps (maximum)
Diagonal viewing angle	74 degrees

Touchpad

Resolution:

Horizontal	1211 dpi
Vertical	1267 dpi
Dimensions:	
Width	4.13 in (105 mm)
Height	3.15 in (80 mm)

Battery

Type	4-cell battery
Dimensions:	
Height	0.30 in (7.72 mm)
Width	4.01 in (101.90 mm)
Depth	10 in (254 mm)
Weight	0.79 lb (0.36 kg)
Voltage	14.8 V
Charging time	4 hours when the computer is powered off.
Operating time	Varies depending on operating conditions and can significantly reduce under certain power-intensive conditions.
Life span (approximate)	300 discharge/charge cycles
Temperature range:	
Operating	0 °C to 35 °C (32 °F to 95 °F)
Storage	–40 °C to 65 °C (–40 °F to 149 °F)
Coin-cell battery	CR-2032

Power Adapter

Types	<ul style="list-style-type: none">• 65 W• 90 W
Input voltage	100 VAC–240 VAC
Input current (maximum)	1.50 A/1.70 A/2.50 A
Input frequency	50 Hz–60 Hz
Output current	3.34 A-4.62 A
Rated output voltage	19.50 VDC
Temperature range:	
Operating	0 °C to 35 °C (32 °F to 95 °F)
Storage	–40 °C to 70 °C (–40 °F to 158 °F)

Computer Environment

Temperature range:	
Operating	0 °C to 35 °C (32 °F to 95 °F)
Storage	–40 °C to 70 °C (–40 °F to 158 °F)
Relative humidity (maximum):	
Operating	10 % to 90 % (non-condensing)
Storage	10 % to 95 % (non-condensing)
Vibration (maximum):	
Measured using a random vibration spectrum that simulates user environment	
Operating	0.66 GRMS
Storage	1.30 GRMS
Shock (maximum):	
Measured with hard drive in operating status and a 2-ms half-sine pulse for operating. Also measured with hard drive in head-parked position and a 2-ms half-sine pulse for storage	
Operating	110 G
Storage	160 G
Altitude (maximum):	
Operating	–15.2 m to 3048 m (–50 ft to 10,000 ft)
Storage	–15.2 m to 10,668 m (–50 ft to 35,000 ft)
Airborne contaminant level	G1 as defined by ISA-S71.04-1985