

8-Port HDMI Splitter - HDMI 2.0, 4K x 2K @ 60 Hz, HDCP 2.2, EDID Management

MODEL NUMBER: **B118-008E-UHD-2**



Splitter with EDID management transmits 4K x 2K video and audio from an HDMI source to eight HDMI displays at the same time.

Features

HDMI Splitter Transmits 4K Video + Audio to 8 HDMI Displays at the Same Time

Recommended for home theaters or short-distance digital signage applications in classrooms, showrooms, offices, churches, restaurants, bars, hotels and trade shows, this Ultra High Definition (UHD) HDMI splitter is quick and easy to install. It connects to an HDMI source device, such as a computer or Blu-ray player, and transmits a 4K audio/video signal to eight HDMI monitors, projectors or televisions simultaneously. You can cascade up to three levels of splitters, which expands the total number of connected displays to 512.

Supports UHD 4K x 2K Signals up to 15 ft. via HDMI Cabling

Using standard 28 AWG HDMI cable, the B118-008E-UHD-2 distributes a 4K x 2K audio/video signal (at 60 Hz) up to 15 feet (4 meters). Be sure the HDMI cables connecting the splitter to the source and displays are no longer than 15 feet. For best performance, we recommend using Tripp Lite's P569-Series Premium High-Speed HDMI cables.

Supports Up-To-Date Features and Formats

The B118-008E-UHD-2 supports a wide range of audio formats, including DTS-HD, Dolby TrueHD, Dolby Digital Plus and LPCM 7.1-channel surround sound. It also features lip sync pass-through, 36-bit Deep Color, xvYCC and x.vColor, while receiving and transmitting up to 18 Gbps of bandwidth with no data loss. To ensure compatibility with the latest hardware, this splitter is compliant with HDCP 2.2, 3D and HDMI 2.0 standards.

User-Adjustable EDID Settings Gives You Control over A/V Resolutions

EDID (Extended Display Identification Data) allows the source device to identify the capabilities of each connected display and transmit to the highest video and audio resolutions shared by all displays. The B118-008E-UHD-2's default EDID setting uses the lowest level of video format shared by the displays (for instance, if two monitors support 4K video and one supports 1080p, all three monitors will show 1080p). In the event you want to override the automatic detection setting and control the audio/video output yourself, you may do so by adjusting the built-in DIP switches.

Ready to Use Right Out of the Package

The plug-and-play B118-008E-UHD-2 requires no additional software or drivers. Connect your devices to the HDMI ports with user-supplied HDMI cables (such as Tripp Lite's P569-Series), and plug the included external power supply into an AC power source to get started. An amber LED indicates the unit is

Highlights

- Transmits up to 15 ft. for digital signage in bars, offices, classrooms, showrooms, etc.
- Supports UHD resolutions up to 4096 x 2160 (@ 60 Hz) for crystal-clear 4K x 2K video
- User-adjustable EDID settings allow compatibility with wide range of TVs/monitors
- Capable of cascading up to 512 total displays in sophisticated applications
- Plug-and-play operation with no software required for easy, immediate installation

Applications

- Watch 4K video content from a notebook, Blu-ray player, cable/satellite box, video game console or media server on multiple televisions or projectors
- Connect a laptop to give a video presentation on multiple 4K screens
- Attach multiple 4K monitors to your PC to allow easier multitasking or more convenient video editing
- Send Ultra HD content to digital signs or point-of-sale displays
- Connect a security camera or other A/V surveillance equipment to multiple displays

System Requirements

- Source device with HDMI output
- Display device(s) with HDMI



receiving power, and blue LEDs indicate connected HDMI inputs. Use the included hardware to install the unit on a desktop or mount it to a wall.

input

Package Includes

- B118-008E-UHD-2 8-Port HDMI 2.0 Splitter
- External power supply with 5 ft. cord & NEMA 1-15P plug (Input: 100–240V, 50/60 Hz, 0.6A; Output: 12V 2A)
- Mounting hardware
- Owner's manual

Specifications

OVERVIEW	
UPC Code	037332239907
INPUT	
External Power Supply Input Specs (V / Hz / A)	100-240V~50/60Hz, 0.6A
External Power Supply Output Specs (V / A)	12V/2A
External Power Supply Cord Length (ft.)	4.9
External Power Supply DC Barrel Connector Specs	OD: 5.5 x 2.1 x 10mm, Positive Pin, Negative Sleeve
External Power Supply Plug(s)	NEMA 1-15P North America
External Power Supply Certifications	UL; cUL
USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	(x1) Amber (Power); (x8) Blue (Signal)
PHYSICAL	
Unit Packaging Type	Box
Unit Dimensions (hwd / in.)	0.87 x 3.19 x 10.35
Unit Weight (lbs.)	1
Unit Weight (kg)	0.45
Material of Construction	Metal
Color	Black



Rackmountable	Yes
ENVIRONMENTAL	
Operating Temperature Range	32 to 140°F (0 to 60°C)
Storage Temperature Range	32 to 140°F (0 to 60°C)
Relative Humidity	0% to 60% RH, Non-Condensing
CONNECTIONS	
Ports	8
Side A - Connector 1	HDMI (FEMALE)
Side B - Connector 1	(8) HDMI (FEMALE)
PORT EXPANSION	
Max Distance (Between any 2 Units)	6ft. (2m)
Max Number of Ports (Entire Chain)	512
FEATURES & SPECIFICATIONS	
Max Supported Video Resolution	4096 x 2160 @60Hz
HDMI Specification	2.0
HDCP Specification	2.2
Audio Specification	DTS-HD, Dolby® TrueHD, Dolby Digital Plus™ and LPCM 7.1 Channel Surround Sound
Max Supported Color Depth	36-bit Deep Color
EDID Compatible	Yes
Technology	HDMI
CERTIFICATIONS	
Certifications	Tested to FCC, RoHS, REACH
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>