

IP-Cam HD Outdoor with LED Floodlight TX-83

WiFi outdoor camera including LED Floodlight lighting






 HD HD Video Resolution 1280x720 / HD Videoauflösung 1280x720	 1/4" CMOS Sensor 1 Megapixel	 6-10m Motion Detection / Bewegungserkennung	 6-8m PIR Sensor
 60dB Sound Detection / Geräuscherkennung	 24 LED Lights / LED Lichter	 6-10m Illuminated viewing area / Ausgeleuchteter Sichtbereich	 Built-in Microphone / Eingebautes Mikrofon
 Built-in Speaker / Integrierter Lautsprecher	 Rotatable Camera Head / Rotierbarer Kamerakopf	 QR Code Scanning (P2P) / QR-Code Scannen (P2P)	 H.264 Dual Video Stream / H.264 Dualer Video Stream



- Video resolution 1280x720 HD with 5-25fps
- Brilliant 1/4" CMOS colour sensor (1 megapixel)
- H.264/MJPEG dual video stream
- Alarm function (automatic E-mail & Push notice)
- Switch ON/OFF the light by APP
- Motion detection 6~10m
- PIR sensor for the LED floodlights 6~8m
- Sound detection 60dB minimum
- Built-in microphone & speaker
- Auto light sensor & 2 LED Floodlights
- 24x LED for 6~10m illuminated viewing area
- Built-in IR-CUT filter for improved day/night vision
- Automatic LED floodlight during PIR detection
- Communication interface 1x RJ45 10M/100M self-adaptive Ethernet
- Supports MicroSD cards up to 64GB
- Direct Smartphone connection via QR-code/P2P
- IP65 camera protection class (against waterjet & dust)
- Easy "do-it-yourself" installation

Technical Specifications:

- Supports 802.11.b/g/n wireless protocol
- Light source: 0.5W / 24x high power LEDs / Ø 650 Lum
- Detection: Angle 70°~80°, Range 6~10m; PIR 6~8m
- Lens: f=3.6mm@F1.2; Horizontal 60.4°
- Shutter 1/50 (1/60) seconds ~ 1/100000 seconds
- Minimum illumination 1.0 Lux@F1.2; AGC ON (0 Lux with IR)
- Video (adjustable): Brightness, Contrast, Sharpness, Saturation
- Video stream 128Kbps~4Mbps
- Audio compression G.711
- Sound detection sensitivity 60dB minimum
- S/N Ratio > 40dB
- Protocol: TCP/IP, HTTP, DHCP, DNS, DDNS, SMTP, NTP, etc.
- Password protection
- Power supply: external power adaptor DC 12V/2A
- Power consumption 16W maximum
- Operating conditions: -10°C~+60°C, humidity 90% or less
- Weight / Dimensions: 1.2kg / (L) 20 x (W) 15 x (H) 20cm (with 40cm antenna)

Package Contents:

- IP-Cam HD outdoor with LED Floodlight TX-83
- Power adapter DC 12V/2A
- Ethernet cable RJ45
- Antenna
- Screws & Dowels & Crossbar
- Pad for the camera foot
- Waterproof cable protection pack
- CD
- User Manual



Article-No. 4662