



Eaton Basic ePDUs

Single-phase power distribution solutions up to 30 amps.

The Eaton® Basic ePDU® product line is designed to provide high reliability power distribution to critical power loads. These units feature a small form factor and lightweight chassis that is easy to mount. Rackmount models feature a rotating mounting bracket that allows for vertical mounting. Vertical models offer blind mount bracket and keyhole button mounting options. The high outlet density and a variety of plug/receptacle configurations make it easy to find a configuration that meets your needs. These configurations are stocked for high availability.

Key features and benefits:

- Cord lengths up to 15 feet
- Rackmount or 24", 48" and 60" lengths for outlet accessibility
- High outlet density up to 36 outlets
- Variable clip foot and button mounting options
- Single-phase 15A to 30A, 120-volt and 240-volt configurations
- UL 60950 approved for IT or data center use



1U RACKMOUNT EPDUS

Catalog Number	Input Plug	Breaker	Max kW	Cord (ft)	Receptacles	Dimensions (H x W x D, in)
EFLXL1500R-PDU1U	5-15P	None	1.44	3	(12) 5-15R	1.7 x 19.0 x 2.4
ePBZ86	5-15P	None	1.44	10	(12) 5-15R	1.7 x 17.3 x 2.3
ePBZ83	5-15P	None	1.44	15	(12) 5-15R	1.7 x 17.3 x 2.3
EFLXL2000R-PDU1U	5-20P	None	1.92	3	(12) 5-20R	1.7 x 19.0 x 2.4
EFLXL2000R-PDU1UL	5-20P	None	1.92	3	(5) L5-20R	1.7 x 19.0 x 3.0
ePBZ85	5-20P	None	1.92	10	(12) 5-20R	1.7 x 17.3 x 2.3
ePBZ99	L5-20P	(1) 20A	1.92	6	(12) 5-20R	1.7 x 19.0 x 2.4
ePBZ82	L5-20P/5-20P*	None	1.92	15	(12) 5-20R	1.7 x 17.3 x 2.3
ePBZ84	L5-30P	(2) 20A	2.88	10	(10) 5-20R	1.7 x 17.0 x 3.5
ePBZ78	L5-30P	(2) 20A	2.88	15	(20) 5-20R	1.7 x 17.0 x 3.5
EFLXI3000R-PDU1UIEC	C20 Inlet	(2) 20A	3.33	3	(12) C13, (1) C19	1.7 x 19.0 x 2.4
ePBZ88	C20	None	3.33	6	(10) C13, (2) C19	1.7 x 19.0 x 2.4
ePBZ95	L6-20P	None	3.33	6	(12) C13, (1) C19	1.7 x 19.0 x 2.4
ePBZ94	L6-30P	(2) 20A	4.99	6	(6) C19	1.7 x 19.0 x 2.4
ePBZ91	L6-30P	(2) 20A	4.99	10	(10) C13	1.7 x 17.0 x 3.5
ePBZ79	L6-30P	(2) 20A	4.99	15	(16) C13, (4) C19	1.7 x 17.0 x 5.1

0U VERTICAL MOUNT EPDUS

Catalog Number	Input Plug	Breaker	Max kW	Cord (ft)	Receptacles	Dimensions (H x W x D, in)
ePBZ75	5-15P	None	1.44	15	(14) 5-15R	23.9 x 1.5 x 1.5
ePBZ98	5-15P	(1) 15A	1.44	6	(18) 5-15R	40.0 x 1.5 x 1.5
ePBZ73	5-15P	(1) 15A	1.44	15	(18) 5-15R	48.0 x 1.5 x 1.5
ePBZ97	5-20P	(1) 20A	1.92	6	(24) 5-20R	48.0 x 1.5 x 1.5
ePBZ96	L5-20P	(1) 20A	1.92	6	(24) 5-20R	48.0 x 1.5 x 1.5
ePBZ74	L5-20P/5-20P*	None	1.92	15	(14) 5-20R	23.9 x 1.5 x 1.5
ePBZ72	L5-20P/5-20P*	(1) 20A	1.92	15	(18) 5-20R	48.0 x 1.5 x 1.5
ePBZ77	L5-20P/5-20P*	(1) 20A	1.92	15	(24) 5-20R	60.0 x 1.5 x 1.5
ePBZ71	L5-20P/5-20P*	(1) 20A	1.92	15	(30) 5-20R	72.0 x 1.5 x 1.5
ePBZ90	L5-30P	(2) 20A	2.88	15	(24) 5-20R	40.0 x 1.9 x 2.1
ePBZ89	C14	None	2.88	6	(16) C13	28.0 x 1.9 x 2.2
ePBZ93	L6-20P	None	3.33	10	(20) C13, (4) C19	40.0 x 1.9 x 2.2
ePBZ92	L6-30P	(2) 20A	4.99	10	(20) C13, (4) C19	42.0 x 1.9 x 2.2
ePBZ80	L6-30P	(2) 20A	4.99	10	(30) C13, (6) C19	52.9 x 1.9 x 2.2

*These units ship with an adapter allowing for 5-20P input plug

To learn more about Eaton's Basic ePDUs, please visit:
www.eaton.com/epdu



Eaton Corporation
 8609 Six Forks Road
 Raleigh, NC 27615
 United States
 800.356.5794

Eaton.com/powerquality

©2011 Eaton Corporation
 All Rights Reserved
 Printed in USA
 PDU34FXA
 November 2011

EATON
 Powering Business Worldwide

Eaton and ePDU are registered trademarks of Eaton Corporation.

All other trademarks are property of their respective owners.