





# DURASCAN® D760



2D/1D Imager



Passport Reader

OCR-A	OCR-B	MICR E-13B
1234ABCD	1 2 3 4 A B C D	1 2 3 4 5 6 7 8 9 0
Alphanumeric (+4 currency char.)	Alphanumeric (+4 currency char.)	Numeric (+4 special char.)


OCR-A / OCR-B / MICR E13B

## Ergonomic, Elegant and Rugged

The DuraScan D760 is a 2D/1D barcode scanner and passport reader with Bluetooth® wireless technology and a highly durable exterior. Built strong for applications in warehouses, outdoor distribution and industrial manufacturing conditions. Scanning 2D/1D barcodes and MRZ/passports, travel merchants need only one device to scan the purchased items and the passport. The scanner's IP54-rated outer casing withstands dust and water splashes, ruggedized for drop protection. Its antimicrobial material is easy to clean, helping protect from germs picked up from daily use. The D760 works perfectly in travel industries, including automotive, healthcare, logistics, and more. Its ergonomic design and light weight fit comfortably in the hand for all day use.



Certified by Apple® for iOS devices (iPad®, iPhone®, iPod Touch®) and compatible with Android and Windows®.



## Features

- **Bluetooth® Wireless Technology** - Compatible with iOS, Android and Windows devices with long-range Bluetooth connection of 330 feet (100m)
- **Certified by Apple® for iOS devices** - Guaranteed Compatibility - With our SDK integrated in over 700+ applications, Socket Mobile scanners are one of the most natively integrated scanners available today. Socket Mobile Scanners are also 100% compatible with any application out-of-the-box in HID (keyboard emulation) mode.
- **Compatible with all Android and Windows devices and applications**
- **Scanning** - Fast 2D & 1D barcode scanning with highly visible and safe LED aimer and omni-directional ability, allowing intuitive rapid scanning. Scans OCR A&B fonts, OCR USC, OCR passport and OCR MICR (E13B) fonts.
- **Exceptional Ergonomics** - Small, light and fits perfectly in the hand for comfortable use over extended periods of time
- **Rugged Design** - Protection rating of IP54 for dust and water splashing protection. Withstands multiple drops to concrete and repeated tumbles
- **Long-Lasting Battery** - Power to last over 16 hours
- **User Indicators** - Intuitive LEDs, Bluetooth connection, battery level and scanning status
- **User Feedback** - Audible tones and hand pulsation
- **Protective Material** - Made with antimicrobial additives to help protect against harmful bacteria
- **Application Integration** - Socket Mobile's Capture SDK enables easy integration in your applications to improve business productivity with fast, efficient and reliable data transfer over Bluetooth wireless technology
- **Wearable** - Includes lanyard/belt clip. Holster and Durable Retractable Clip available (sold separately)
- **Designed and Assembled in the USA**
- **Developer Support Available**
- **1-Year Warranty**

**Default Barcode Symbologies:** 1D Symbologies: Codabar, Code 39, Code 93, Code 128, EAN-13/JAN, EAN-8/JAN, GS1 Databar, GS1 Databar Expanded, GS1 Databar Limited, GS1-128, Interleaved 2 of 5, ISBT 128, UPC A, UPC EO  
 2D Symbologies: Aztec, Data Matrix, Maxicode, Micro PDF417, PDF417  
**Postal Codes:** Australia Post  
**OCR Typeface:** OCR B Passport - 2 lines


**Supported Barcode Symbologies:** 1D Symbologies: Bookland EAN, Chinese 2 of 5, Codabar, Code 11, Code 39, Code 93, Code 128, Composite CC-A/B, Composite CC-C, Composite TLC, Discrete 2 of 5, EAN-13/JAN, EAN-8/JAN, GS1 Databar, GS1 Databar Expanded, GS1 Databar Limited, GS1-128, Interleaved 2 of 5, ISBT 128, ISSN EAN, Matrix 2 of 5, MSI, UPC/EAN/JAN, UPC A, UPC EO  
 2D Symbologies: Aztec, Data Matrix, Maxicode, Micro PDF417, MicroQR, PDF417, QR Code  
**Postal Codes:** Australia Post, Han Xin, Japan Postal, KIX Code, Maxicode, Netherlands, UPU FICS Posta, US Planet, US Postnet, USPS 4CB/One Code/Intelligent Mail  
**OCR Type Face:** OCR-A, OCR-B, MICR-E13B, US currency serial number

**Scan Angle:** 42° (Horizontal) - 28° (Vertical)

**Sensor Resolution:** 640 horizontal x 400 vertical pixels

**Print Contrast:** Down to 25%-20%

**Reading Distance:**



4.6 to 76.2 cm (1.8 to 30.0 in.) Depends on barcode size, symbology, label media, Narrow and Wide ratio, scan angle

**Decode Ranges**

	Near	Far
4 mil Code 39	3.3 in/8.4 cm	8.8 in/22.4 cm
5 mil Code 128	2.8 in/7.1 cm	8.2 in/20.8 cm
5 mil Code 39	2.0 in/5.08 cm	13.5 in/34.3 cm
10 mil Data Matrix	2.9 in/7.4 cm	10.1 in/25.7 cm
100% UPC A	1.8 in/4.6 cm*	26.0 in/66.0 cm
20 mil Code 39	2.0 in/5.08 cm*	30.0 in/76.2 cm

**Technology:** 2D/1D Barcode Imager & OCR character reader

**Light Source:** Hyper Red 660 nm (nanometer) LED

**Aimer:** 610 nm LED

Battery:	1400 mAh Lithium - Ion Battery
Charge Time:	6 Hours
Battery Life - Per Full Charge:	Standby time: over 20 hours Active Scan Time: 85,000 scans within 9 hours (based on 2 scans every 1 second) 17,000 scans within 19 hours (based on 1 scan every 4 seconds)
Note:	Battery life varies depending on ambient temperature, ambient light and age of battery.

## BLUETOOTH (WIRELESS CONNECTION)

Bluetooth Radio:	Class 1 Bluetooth, version 2.1 + EDR (Enhanced Data Rates) with 56-bit data encryption
Bluetooth Range:	Up to 100 m (330 ft.) depending on environment, range limit is usually due to the Host Device (phone, tablet or notebook)
Bluetooth Profiles:	Basic Mode - Human Interface Device (HID)*, Application Mode - Serial Port Profile (SPP) and Application Mode - MFi-SPP. Some Operating Systems or smartphone/tablet models may support only one profile. <i>*By default, the scanner is set to Basic Mode (HID).</i>

## PHYSICAL CHARACTERISTICS



### Intuitive LED Indicators

- Battery LED: Green, Amber and Red
- Bluetooth LED: Blue
- Scan LED: Green and Red

**Weight/Mass**  
• 4.0 oz. (112.5 g)



### Power Button

- On/Off (enabled on-screen keyboard) in Basic Mode

### Scan Button

Ambient Light:	From 0 to 100 000 lux, From pitch black to direct sun light
Operating Temperature:	0° to 45° C (32° to 113° F)
Storage Temperature:	-5° to 70° C (-22° to 158° F)
Relative Humidity:	95% at 60° C (140° F) (non-condensing)
Sealing:	IP54 (Ingress Protection rating for dust and water) EN60529
Drop Specifications:	Multiple 5 ft. drops to concrete
Tumble Specification:	250 cycles at 1.64 ft. (0.5 m) (500 drops), IEC60068-2-31, IEC60068-2-32

## OPERATING SYSTEM COMPATIBILITY

Android OS - Basic Mode (HID)* & Application Mode (SPP)	Mac OS and Linux - Basic Mode (HID)* only
Apple iOS - Basic Mode (HID)* & Application Mode (MFi-SPP)	Windows OS - 10, 8, and 7 - Basic Mode (HID)* & Application Mode (SPP)
Compatible with devices supporting Basic Mode (HID)* protocol	Supported Language Setting in Basic Mode (HID): English, French, German and Spanish

*\*By default the scanner is in Basic Mode (HID). No software installation required.*

Certified by Apple® for iOS devices (iPad®, iPhone®, iPod Touch®) and compatible with Android and Windows®.



## CERTIFICATION & REGULATORY

Bluetooth SIG:	Declaration ID: D030473 QD ID: 82009
Electrical Safety:	Certified to IEC 60950-1, UL 60950-1, CAN/CSA C22.2
Environmental:	Environmental: RoHS EN 50581
EMI / RFI:	FCC Part 15 Class C, RSS 210, iCES 003, C-Tick, CISPR 22, CE EN55022, EN55024, TELEC FCC ID: T9J-RN41-3 IC ID: 6514A-RN413 Telec ID:  201-135280
LED Safety:	IEC 62471, EN 62471 (EXEMPT GROUP)



## WARRANTY

Scanner:	Standard one year limited warranty
Accessories:	90 days
Extended Warranty: (sold separately)	<a href="http://www.socketmobile.com/socketcare">www.socketmobile.com/socketcare</a>




## COMMON USES

Retail/Point of Sale	Warehouse management	Transportation
Office use	Shipping & Receiving	Gaming
Healthcare	Field Sales/Service	
Mobile Tracking	Banking	



- (1) DuraScan D760, 2D/1D Barcode Imager
- (1) Charging Cable
- (1) Lanyard
- (1) Get Started Insert



Socket Mobile Companion  
Download for Free!

The D760 is available in 3 colors:

- Utility Gray (SKU# CX3435-1890)
- Safety Green (SKU# CX3437-1892)
- Construction Orange (SKU# CX3438-1893)

## OPTIONAL ACCESSORIES

Charging Stand  
SKU# AC4076-1538



Great for using Presentation Mode

Charging Cradle  
SKU# AC4102-1695



Perfect for wall mounting

Charging Dock  
SKU# AC4133-1871



Ideal as a desktop charger

Durable Retractable Clip  
AC4130-1828



Provides quick access to scanner

Holster  
AC4131-1829



Safe and accessible placement

Lanyard - Black  
SKU# AC4100-1692



Great for hanging around your neck

socketmobile.com

Toll-Free: +1 800 552 3300 (USA/Canada)

France: +33 970 462 241

Latin America: +1 510 933 3153

sales@socketmobile.com

Asia Pacific: +1 510 933 3122

Germany: +49 9401 5299 052

Switzerland: +41 62 834 07 80

EMEA & Russia: +41 62 834 0780

Japan: +8190 9808 0518

UK/Ireland/South Africa: +44 (0) 1252 761403  
+44 7787 112109