

VGA to RCA and S-Video Converter - USB Power

Product ID: VGA2VID2



This VGA to RCA/S-Video converter box provides a simple way to convert and scale a 1080p VGA video input signal to a 480i composite (CVBS) or S-Video output signal. Perfect for use with legacy projectors or TV sets.

Hassle-Free Setup and Easy to Use

Equipped with a NTSC/PAL toggle switch and a scan button for simple configuration and selection of your video output settings, this compact VGA to Composite and S-Video adapter installs quickly and easily, for a true plug-and-play experience.

Save on Upgrade Costs

By using this VGA to AV adapter you can connect a PC's VGA connector to legacy TVs and projectors, ultimately saving the costs of upgrading your equipment. It's ideal for boardroom settings, medical imaging and watching videos on your S-Video or Composite display.

Crystal-Clear Picture Quality

The PC to television converter features an integrated video scaler circuit that dynamically converts VGA video input signals with resolutions up to 1920x1200 @ 60Hz. To ensure compatibility with your display or projector the computer to TV converter outputs high quality 720 x 480 video, the highest supported by S-Video or Composite.

VGA2VID2 is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Great for boardroom meetings, tradeshow, lectures, and CRT digital signage solutions
- An inexpensive way to increase the size of a computer display
- Displays computer screen images on your TV or Projector

Features

- Provides output in both Composite and S-Video formats
- Supports PC input resolutions up to 1920 x 1080
- Select between NTSC and PAL outputs
- Dynamically adjust image underscan and overscan
- Powered by USB port

Hardware	Warranty	2 Years
	Active or Passive Adapter	Active
	Audio	No
	AV Input	VGA
	AV Output	Composite S-Video
Performance	Supported Resolutions	Input - Up to 1920x1080 60Hz Output - 640x480 60Hz
Connector(s)	Connector A	1 - VGA (15 pin, High Density D-Sub) Female Input
	Connector B	1 - S-Video (4 pin, Mini-DIN) Female Output 1 - Composite Video (1 x RCA) Female Output
Power	Plug Type	USB Mini-B (5 pin)
	Power Consumption (In Watts)	2.5W
	Power Source	USB-Powered
Environmental	Humidity	5 to 90 % RH
	Operating Temperature	0 to 50°C (32 - 122°F)
	Storage Temperature	-10 to 80°C (14 to 176°F)
Physical Characteristics	Color	Black
	Product Height	20.000
	Product Length	60.500
	Product Width	54.000
	Weight of Product	35.000
Packaging Information	Package Height	24.000
	Package Length	105.000
	Package Width	133.000
	Shipping (Package) Weight	40.000
What's in the Box	Included in Package	1 - VGA to S-Video and Composite Adapter 1 - Mini USB Power Cable 1 - Quick-Start Guide

Product appearance and specifications are subject to change without notice.