



FCS-3085 Version: 1

Zoom Dome Outdoor Network camera, 4-Megapixel, Outdoor, 802.3af PoE, day & night, IR LEDs, WDR, Varifocal

Key Features

- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Weatherproof IP66-rated with wide operating temperature (-30°C to 60°C) for harsh environments
- Built-in Micro SDHC/SDXC card slot for local storage
- Built-in infrared LEDs for night viewing up to 30m
- Removable IR-cut filter for day and night surveillance
- Vandal-proof IK10-rated housing
- Compression: H.264/MJPEG
- Power support: PoE (IEEE 802.3af)
- Free video surveillance and CMS (Central Management System) software with 64-channel license

Specifications

System Specifications

Standards & Protocols:

TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour

Image Sensor:

1/3" Progressive Scan CMOS

Connectors and Cabling:

1 x RJ-45 10/100 Mbps PoE port

Power Connector

Audio:In/Out

I/O terminal block (1 DI/1 DO)

1 x MicroSDHC/ MicroSDXC card slot

Button/Knob:

Reset Button

Indicator:

Power

**Lens:**

2.8 - 12 mm @ F1.4,

IR Cut Filter:

IR cut filter with auto switch

IR LED:

Up to 30m

Shutter Time:

1/3 s ~ 1/10,000 s

Angle of View:

112°~33.8°

Video Compression:

H.264/MJPEG/H.264+

Resolution:

50Hz: 20fps (2688×1520), 25fps(1920×1080), 25fps(1280×720)

60Hz: 20fps (2688×1520), 30fps (1920×1080), 30fps(1280×720)

Video Format:

RAW

Audio Compression:

G.711/G.722.1/G.726/MP2L2, 64Kbps(G.711) / 16Kbps(G.722.1) / 16Kbps(G.726) / 32-128Kbps(MP2L2)

Power Input:

12V DC±10%, PoE (802.3af)

Power Consumption:

Max. 5.5 W

Features

General:

Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser

PoE:

PoE (802.3af Class3)

Security:

One-key reset, Anti-Flicker, heartbeat, mirror, password protection, privacy mask, Watermark, IP address filtering, Anonymous access

Video:

Line Crossing, Intrusion Detection, Motion detection, Dynamic analysis, Tampering alarm, Network disconnect , IP address conflict, Storage exception

Audio:

G.711/G.722.1/G.726/MP2L2

Performance

Number of Clients:

10

Data Transfer Rate:

32Kbps~16Mbps

Storage Capacity:

Support Micro SD/SDHC/SDXC card with ANR (up to 128G)

Frame Rate:

50Hz: 20fps , 25fps, 25fps

60Hz: 20fps , 30fps ,30fps

Minimum illumination:

0.01Lux @(F1.2,AGC ON), 0.014 Lux @(F1.4,AGC ON), 0 Lux with IR

Environment

Temperature (°C):

-30 °C ~ 60 °C (-22 °F ~ 140 °F)

Humidity (Non-condensing):

Humidity 95% or less (non-condensing)

Physical Specifications

Dimensions (W x D x H mm):

140

Weight (g):

140

Color:

99.0

Approval and Compliance

EMI/EMS:

CE,FCC

Environmental Test:

IEC60068-2-75Eh, 50J; EN50102, IK10

Others:

ONVIF (Profile S, Profile G), PSIA, CGI, ISAPI

Others

Operation Systems:

Microsoft Windows 10/8/7/Vista/XP/

Viewing Systems:

IE

Order Information

FCS-3085

Package Contents

FCS-3085

Screw Kit

Resource CD (User Manual, Utility, QIG)

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.