


Overview

The HP Ethernet 1Gb 4-port 366FLR features the next generation of Ethernet integration offering in a single chip solution on a FlexibleLOM form factor, further reducing power requirements for 4 ports of 1Gb Ethernet. The HP 366FLR is the PCI Express 2.1 x4 based on the latest Intel® Ethernet Controller I350 designed for use with select HP ProLiant Gen8 rack and scalable servers. Its FlexibleLOM form factor means customers now have choice to meet growing infrastructure needs.

The HP 366FLR adapter supports advanced features such as Large Send offload capability, TCP checksum and segmentation, VLAN tagging, MSI-X, Jumbo frames, IEEE 1588, and virtualization features such as Intel Virtualization Technology for Connectivity, VMware NetQueue, Microsoft VMQ and WOL, and power management technologies like Energy Efficient Ethernet.



Models

HP Ethernet 1Gb 4-port 366FLR Adapter

665240-B21

Kit contents

- HP Ethernet 1Gb 4-port 366FLR Adapter
- Quick install card
- Product warranty statement

Compatibility

Servers

ProLiant DL (rack-optimized):

- HP ProLiant DL160 Gen8
- HP ProLiant DL360p Gen8
- HP ProLiant DL380p Gen8
- HP ProLiant DL385p Gen8
- HP ProLiant DL560 Gen8

ProLiant SL (scalable):

- HP ProLiant SL210t Gen8
- HP ProLiant SL230 Gen8
- HP ProLiant SL250 Gen8
- HP ProLiant SL270 Gen8

NOTE: This is a list of supported servers. Some servers may be discontinued.

Standard Features

Performance

Product Features

- FlexibleLOM for select HP Gen8 Rack servers
- Industry-leading hardware integration for low power
- Quad-port 1GbE provides up to 8Gb/s full duplex throughput per adapter
- Energy Efficient Ethernet (EEE) support
- Optimized for virtual servers
- Improved small packet performance
- Support for Preboot eXecution Environment (PXE)

Quad-port 1 Gigabit Ethernet Throughput

The HP 366FLR adapter provides 8 Gbps aggregate full duplex, delivering outstanding network performance that improves response time and removes bottlenecks. Four ports on a single adapter are ideal for high density, I/O slot constrained servers, virtualization, security, applications, server consolidation, and increased network segmentation. The 8Gbps full-duplex aggregate throughput meets the needs for customers desiring high bandwidth but are not yet ready to move to 10 Gigabit Ethernet. **NOTE:** Port enumeration on the 366FLR is from the bottom up, i.e. the port closest to the gold teeth is port #1 and the port near the top of the adapter is port #4.

Jumbo Frames

The HP 366FLR FlexibleLOM supports jumbo frames, permits up to a 9.5K byte (KB) transmission unit (MTU) when running Ethernet, which is over five times the size of standard 1500-byte Ethernet frame. Jumbo frames can help achieve higher throughput and better CPU utilization and are particularly useful for database transfer and tape backup operations.

MSI and MSI-X

Up to 25 Message Signaled Interrupt (Extended) vectors per port provides performance benefits for multi-core servers by load balancing interrupts between CPUs/cores.

802.1Q VLANs

IEEE 802.1Q virtual local area network (VLAN) protocol allows each physical port of the HP 366FLR to be separated into multiple virtual NICs for added network segmentation and enhanced security and performance. VLANs increase security by isolating traffic between users. Limiting the broadcast traffic to within the same VLAN domain also improves performance.

TCP/IP Stateless Offloading

For overall improved system response, the HP 366FLR supports TCP, IPv4, UDP checksum offload, Large Send Offload (LSO), and Segmentation Offload (TSO). These features optimize host efficiency, leaving the CPU available for other duties.

Time synchronization (IEEE 1588)

Hardware assist for IEEE 1588 and IEEE 802.1AS time synchronization implementations for time sensitive applications.

Optimized for Virtualization

Intel Virtualization Technology for Connectivity provides I/O Virtualization support for VMware NetQueue and Microsoft VMQ help meet the performance demands of consolidated virtual workloads.

Energy Efficient Ethernet

Compliant with IEEE 802.3az, featuring advanced power savings by throttling power usage with network load activity (with compatible link partner).

Standard Features

HP Sea of Sensors 3D Support for HP Sea of Sensors 3D which is a collection of 32 sensors that automatically track thermal activity - heat - across the server. When temperatures get too high, sensors can kick on fans and make other adjustments to reduce energy usage. What makes it better is the upgrade from all six fans kicking on at one time to a new system where only one kicks on - the one in proximity of the area that started heating up - thus reducing the amount of energy used for cooling.

HP Active Health System Supports HP Active Health System monitors and records changes in the server hardware and configuration enabling customers to have accurate information that will assist in diagnosing problems and delivering rapid resolution when server failures occur.

Versatility

10/100/1000T Twisted Pair Networks In addition to Gigabit Ethernet, the 366FLR adapter supports both 10Mbps and 100Mbps providing compatibility with Ethernet and Fast Ethernet twisted pair networks.

FlexibleLOM slot Compatibility The HP 366FLR is compatible only with HP FlexibleLOM slot available on select HP ProLiant Gen8 rack and scale-out servers.

High Availability

Network Adapter Teaming ProLiant Network Adapter Teaming provides fault tolerance and load balancing across a team of two or more network adapters. The team of adapters works together as a single virtual adapter. The HP 366FLR FlexibleLOM provides support for several different types of teaming. The teaming options offer IT professionals an easy, efficient, and cost-effective way to provide network fault tolerance and increased network bandwidth. For more information, refer to the ProLiant Network Adapter Teaming Whitepaper available at: <http://bizsupport.austin.hp.com/bc/docs/support/SupportManual/c01415139/c01415139.pdf>

Network Management

Auto-negotiation The HP 366FLR automatically senses the speed of the device to which it is attached. It also automatically configures for full duplex, depending on the duplex mode of the switch, hub, or router connected to the adapter.

Management Support Like all HP server adapters, the HP 366FLR ships with drivers and agents that can be managed from HP Systems Insight Manager, as well as using any other management application that supports SNMP. HP Systems Insight Manager can recognize the 366FLR individually or in teams, and can collect and report SNMP statistics on the adapter events.

Server Integration The HP 366FLR is a completely integrated, tested, and qualified solution that is optimized for HP servers. HP validates a wide variety of major operating systems drivers with the network drivers plus provides central interface to simplify network management.

Standard Features

Configuration Utilities	Each HP 366FLR ships with a suite of operating system-tailored configuration utilities that allow the user to enable initial diagnostics and configure adapter teaming. This includes a patented teaming GUI for Microsoft Windows operating systems. Additionally, support for scripted installations of teams in a Microsoft Windows environment allow for unattended OS installations.
LED Indicators	Per port LED indicators show link integrity, network activity, and network speed for easy troubleshooting. Colored LEDs on each port of the HP 366FLR adapter indicate network activity, and network link speed. Green link LED indicates 10/100/1000Mb speed.
PXE	Support for pre-boot execution environment (PXE) enables automatic deployment of computing resources remotely from anywhere. It allows a new or existing server to boot over the network and download software, including the operating system, from a management/ deployment server at another location on the network. Additionally, PXE enables decentralized software distribution and remote troubleshooting and repairs. The HP 366FLR supports PXE.
Warranty	Additional information regarding worldwide limited warranty and technical support is available at: http://h18004.www1.hp.com/products/servers/platforms/warranty/index.html

Service and Support

Service and Support

HP Technology Services

HP Technology Services offers you consultants and support experts to solve your most complex infrastructure problems. We help keep your business running, boost availability and avoid downtime.

Protect your business beyond warranty with HP Care Pack Services

When you buy HP Options, it's also a good time to think about what level of service you may need. HP Care Pack services provide total care and support expertise with committed response choices designed to meet your IT and business need.

HP Foundation Care services deliver scalable support-packages for HP industry-standard servers and software. You can choose the type and level of service that is most suitable for your business needs. New to this portfolio is HP Collaborative Support. If you are running business critical environments, HP offers Proactive Care or Critical Advantage. These services help you deliver high levels of application availability through proactive service management and advanced technical response.

Here is the support service recommendation from the Foundation Care and Proactive Care portfolio. For customized support service solution, HP can work with you to tailor a service solution for your unique support requirements using broader services portfolio of Foundation Care and Proactive Care.

Recommended HP Care Pack Services for optimal satisfaction with your HP product

Recommended Services **3-Year HP 24x7 4 hour Response, Hardware Support Onsite Service**

Provides you with rapid remote support and if required an HP authorized representative who will arrive on site any time and day of the year to begin hardware maintenance service within 4 hours of the service request being logged.

<http://h20195.www2.hp.com/V2/GetPDF.aspx/5982-6547EEE.pdf>

OR

3-Year HP 24x7 4 hour Response, HP Collaborative Support

Offers customers a single point of contact for server problem diagnosis, hardware problem resolution, and basic software problem diagnosis, fault isolation, and resolution if available to HP. If the problem is with HP HW, the representative will arrive on site any time and day of the year to begin hardware maintenance service within 4 hours of the service request being logged. In case, the issue is with HP or supported third-party software product and cannot be resolved by applying known fixes, HP will contact the third-party vendor and create a problem incident on your behalf.

HP ProLiant Server Hardware Installation

Provides for the basic hardware installation of HP branded servers, storage devices and networking options to assist you in bringing your new hardware into operation in a timely and professional manner.

<http://h20195.www2.hp.com/V2/GetPDF.aspx/5981-9356EN.pdf>

Service and Support

Related HP Care Pack Services to enhance your HP product experience

Related Services

3-Year HP 24x7 4 hour Response, Proactive Care or Critical Advantage

Helps optimize your systems and delivers high levels of application availability through proactive service management and advanced technical response. A skilled Technical Manager will own your query or issue end to end until resolved, delivering a single point of contact for you.

<http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA3-2140ENW.pdf>

OR

3-Year HP 6-hour Onsite Call-to-Repair, HP Collaborative Support

Offers customers a single point of contact for server problem diagnosis, hardware problem resolution to return the hardware in operating condition within 6 hours of the initial service request to the HP Global Solution Center, and basic software problem diagnosis, fault isolation, and resolution if available to HP. In case, the issue is with HP or supported third-party software product and cannot be resolved by applying known fixes, HP will contact the third-party vendor and create a problem incident on your behalf.

HP Proactive Select Service

Provides a flexible way to purchase HP best-in-class consultancy and technical services. You can buy Proactive Select Service Credits when you purchase your hardware and then use the credits over the next 12 months.

<http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA2-3842ENN.pdf>

Insight Remote Support

Provides 24 X 7 remote monitoring, proactive notifications, and problem resolution. Learn more

<http://www.hp.com/go/insightremotesupport>

HP Support Center

Personalized online support portal with access to information, tools and experts to support HP business products. Submit support cases online, chat with HP experts, access support resources or collaborate with peers. Learn more <http://www.hp.com/go/hpsc>

HP's Support Center Mobile App* allows you to resolve issues yourself or quickly connect to an agent for live support. Now, you can get access to personalized IT support anywhere, anytime.

HP Insight Remote Support and HP Support Center are available at no additional cost with a HP warranty, HP Care Pack or HP contractual support agreement.

*HP' Support Center Mobile App is subject to local availability.

Parts and materials

HP will provide HP-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements. Supplies and consumable parts will not be provided as part of this service; standard warranty terms and conditions apply. Parts and components that have exceeded their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual or the technical product data sheet will not be provided, repaired or replaced as part of this service.

Service and Support

Warranty / Service Coverage

For ProLiant servers and storage systems, this service covers HP-branded hardware options qualified for the server, purchased at the same time or afterward, internal to the enclosure, as well as external monitors up to 22" and tower UPS products; these items will be covered at the same service level and for the same coverage period as the server unless the maximum supported lifetime and/or the maximum usage limitation has been exceeded. Coverage of the UPS battery is not included; standard warranty terms and conditions apply.

The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by HP due to malfunction. It does not apply to any exchange of Disk or SSD/Flash Drives that have not failed. SSD/Flash Drives that are specified by HP as consumable parts and/or that have exceeded maximum supported lifetime and/or the maximum usage limit as set forth in the manufacturer's operating manual or the technical data sheet are not eligible for the defective media retention service feature option.

For more information

To learn more on services for HP ESSN Options, please contact your HP sales representative or HP Authorized Channel Partner. Or visit: <http://www.hp.com/services/proliant> or www.hp.com/services/bladesystem

Related Options

Gigabit Server Adapters	HP NC112T PCI Express Gigabit Server Adapter	503746-B21
	HP NC360T PCI-E Dual Port Gigabit Server Adapter	412648-B21
	HP NC364T PCI-E Quad Port Gigabit Server Adapter	435508-B21
	HP NC365T 4-port Ethernet Server Adapter	593722-B21
	HP NC373F PCI-E Multifunction 1000SX Gigabit Svr Adapter	394793-B21
	HP NC373T PCI-E Multifunction Gigabit Server Adapter	394791-B21
	HP NC375T PCI Express Quad Port Gigabit Server Adapter	538696-B21
	HP NC382T PCI Express Dual Port Multifunction Gigabit Server Adapter	458492-B21
	HP Ethernet 1Gb 4-port 331T Adapter	647594-B21
	HP Ethernet 1Gb 2-port 361T Adapter	652497-B21
HP Ethernet 1Gb 2-port 332T Adapter	615732-B21	

10 Gigabit Server Adapters

NOTE: A minimum of two Gigabytes (2 GB) of server memory is required per each adapter.

HP NC522SFP Dual Port 10GbE Gigabit Server Adapter	468332-B21
HP NC523SFP 10Gb 2-port Server Adapter	593717-B21
HP NC524SFP Dual Port 10GbE Module	489892-B21
NOTE: NC524SFP is available only on DL370 G6, ML370 G6, DL580 G7, DL585 G7, and DL980 G7.	
HP NC550SFP Dual Port 10GbE Server Adapter	581201-B21
HP NC552SFP 10Gb 2-port Ethernet Server Adapter	614203-B21
HP Ethernet 10Gb 2-port 530SFP Adapter	652503-B21
HP Ethernet 10Gb 2-port 530T Adapter	656596-B21
HP Ethernet 10Gb 2-port 560SFP+ Adapter	665249-B21
HP Ethernet 10Gb 2-port 561T Adapter	716591-B21
HP Ethernet 10Gb 2-port 570SFP+ Adapter	718904-B21

FlexibleLOM Adapters

NOTE: A minimum of two Gigabytes (2 GB) of server memory is required per each adapter.

Ethernet Adapters

HP Ethernet 1Gb 4-port 331FLR Adapter	629135-B21
HP Ethernet 10Gb 2-port 530FLR-SFP+ Adapter	647581-B21
HP Ethernet 10Gb 2-port 560FLR-SFP+ Adapter	665243-B21
HP Ethernet 10Gb 2-port 561FLR-T Adapter	700699-B21
HP Ethernet 10Gb 2-port 570FLR-SFP+ Adapter	717491-B21

FlexFabric Adapters

HP FlexFabric 10Gb 2-port 526FLR SFP+ Adapter	629138-B21
HP FlexFabric 10Gb 2-port 533FLR-T Adapter	700759-B21
HP FlexFabric 10Gb 2-port 534FLR-SFP+ Adapter	700751-B21
HP FlexFabric 10Gb 2-port 554FLR-SFP+ Adapter	629142-B21

NOTE: Please see the QuickSpecs for Technical Specifications and additional information: www.hp.com/go/ProLiantNICs

Technical Specifications

General Specifications	Network processor	Intel® Ethernet Controller I350	
	Data rate	Four 1GbE ports, each at 2 Gbps full duplex; 8 Gbps aggregate full duplex theoretical bandwidth. 10/100/1000 Mbps, Full-duplex	
	Data path	Four lane (x4) PCI Express, mechanically compatible with x8 and x16 FlexibleLOM slots	
	Bus type	PCI Express v2.0 (Gen2.1 x4) (FlexibleLOM slot)	
	Connector	RJ-45 (Four)	
	Cable distance	Up to 328 ft (100 m)	
	Wiring	Category 5e (CAT-5e) or better twisted-pair cabling	
	Dimensions	11.75 cm x 7.62 cm [4.626 in x 3.0 in (L x W)] (without bracket)	
	IEEE Compliance	802.3, 802.3ab, 802.3u, 802.3x, 802.3ad, 802.1q, 802.3az, 1588, 802.1as	
	Form factor	FlexibleLOM	
Power and Environmental Specifications	Operating	Temperature 32° to 131° F (0° to 55° C) Humidity 10% to 90% non-condensing	
	Non-operating	Temperature -85° to 185° F (-65° to 85° C) Humidity 5% to 95% non-condensing	
	Power requirement	5.5W Maximum	
	Emissions classification	Class A	
	Agency Approvals	USA	FCC Part 15 Class A
		Canada	ICES---3, Issue 4
		Japan	VCCI V3 (2010.04) Class A
		Korea	KN22 Class B, KN24
		Australia	EN55022:2006+A12007 class A
		International	EN55022:2006 + A1:2007 Class A EN55024:1998+A1:2011+A2; EN61000-3-2:2006, EN61000-3-3:2008
RoHS Compliance	6 of 6		
Safety	UL Mark (USA and Canada)		
	CE Mark		
	EN 60590-1		
Operating System Support	<ul style="list-style-type: none">● Microsoft Windows Server 2008 (32/64), Enterprise, Server 2012● Web, Embedded, and R2● Microsoft Windows HPC Server 2008● Microsoft Windows 2008 Standard (32 and x64)● Microsoft Windows 2008 Enterprise (32 and x64)● Microsoft Windows Small Business Server 2011 (SBS V7) - base● Microsoft Windows Small Business Server 2011 Essentials● RHEL 5.7 x86 and AMD 64 & EM 64T● RHEL 6.1 x86 and AMD 64 & EM 64T● SLES10: x86 and AMD 64 & EM 64T● SLES 11: x86 and AMD 64 & EM64T● Solaris 10		

Technical Specifications

- VMWare vSphere 4.1 and 5.0
- Citrix
- HyperV (Windows Server 2008 32 and 64)

NOTE: For more Linux OS support & certification information, please visit the ProLiant & Bladesystem Server Linux matrix: <http://h18004.www1.hp.com/products/servers/linux/hplinuxcert.html>

Environment-friendly Products and Approach

End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return, trade-in, and recycling programs in many geographic areas. For trade-in information, please go to: <http://www.hp.com/go/green>. To recycle your product, please go to: <http://www.hp.com/go/green> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <http://www.hp.com/go/green>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

© Copyright 2013 Hewlett-Packard Development Company, L.P.

The information contained herein is subject to change without notice.

Windows is a US registered trademark of Microsoft Corporation.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.