



CP350SLG Standby UPS

Offers energy savings, battery backup and surge protection.

The CyberPower Standby CP350SLG uninterruptible power supply (UPS) safeguards PCs and other electronics (monitors, cable DSL/ modems, VoIP routers, fax machines, and home theater equipment) from blackouts, brownouts, surges, spikes, sags, and other power abnormalities.

This UPS system is ENERGY STAR® qualified with patented GreenPower UPS™ High Efficiency circuitry to save on energy costs by reducing energy consumption and heat buildup.

A Three-Year Warranty ensures that this UPS has passed our highest quality standards in design, assembly, material and workmanship, further protection is offered by a \$75,000 Connected Equipment Guarantee.

Typical Applications

- Desktop Computers
- Personal Electronics

Features

- 350VA / 225W
- Standby Topology
- GreenPower UPS™
- ENERGY STAR® Qualified
- Full-time Surge Protection and Battery Backup
- Compact Form Factor
- 6 Outlets with RJ11 Protection
- EMI/RFI Filters
- 3-Year Warranty

CP350SLG Standby UPS

Offers energy savings, battery backup and surge protection.

GENERAL	
UPS Topology	Standby
Energy Saving	GreenPower UPS™ High Efficiency
ENERGY STAR® Qualified	Yes
INPUT	
Voltage	96Vac - 140Vac
Frequency	47Hz - 63Hz
Surge Protection	10 Amp
Plug Type	NEMA 5-15P
Plug Style	Right Angle, 45 Degree Offset Right
Cord Length	5'
OUTPUT	
VA	350
Watts	255
On Battery Voltage	120Vac ± 5.0%
On Battery Frequency	50/60Hz ± 1%
On Battery Waveform	Simulated Sine Wave
Outlet Type	NEMA 5-15R
Outlets - Total	6
Outlets - Battery & Surge Protected	3
Outlets - Surge-Only Protected	3
Outlets - Widely Spaced	2
Overload Protection	Internal circuitry limiting / circuit breaker
Transfer Time	4ms
BATTERY	
Runtime at Half Load (min)	8
Runtime at Full Load (min)	2
Battery Type	Sealed Lead-Acid
Battery Size	12V/3.6AH
Battery Quantity	1
User Replaceable	No
Typical Recharge Time	8 Hours
SURGE PROTECTION & FILTERING	
Surge Suppression	810 Joules
Phone Protection RJ11	1-In, 1-Out
EMI/RFI Filtration	Yes

MANAGEMENT & COMMUNICATIONS	
HID Compliant USB Port	No
Serial Port	No
Cable Management	None
LED Indicators	Power On, Wiring Fault
Audible Alarms	Battery Mode, Battery Low, Overload, UPS Fault, Replace Battery
Software	None
PHYSICAL	
Form Factor	Compact
Keyhole Mounting Slots	No
Dimensions (WxHxD) (in.)	7.1 x 4.3 x 3.2
Weight (lbs.)	3.5
ENVIRONMENTAL	
Operating Temperature	32°F to 104°F / 0°C to 40°C
Operating Relative Humidity	0% - 90% non-condensing
CERTIFICATIONS	
Safety	UL1778, cUL 107.3, FCC DOC Class B
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	3 Years Limited
Connected Equipment Guarantee	Lifetime
CEG Amount	\$75,000