

### Technical Specifications

#### Models

##### Smart AC Adapters

HP 45W Smart AC Adapter (4.5mm)	H6Y88AA
HP 65W Smart AC Adapter (4.5mm)	H6Y89AA
HP 90W Smart AC Adapter (4.5mm)	H6Y90AA
HP 150W Smart AC Adapter (4.5mm)	W2F74AA
HP 200W Smart AC Adapter (4.5mm)	W2F75AA

##### Slim AC Adapters

HP 65W Slim AC Adapter	H6Y82AA
HP 90W Slim AC Adapter	H6Y83AA

##### Specialized Travel Adapters

HP 65W Smart Travel AC Adapter	JOE43AA
HP 90W Slim Combo Adapter with USB	H6Y84AA

##### USB-C AC Adapters

HP 45W USB-C™ AC Adapter	V5Y26AA
HP 45W USB-C G2 Power Adapter	1HE07AA
HP 45W USB-C LC Power Adapter	1MZ01AA
HP 65W USB-C Power Adapter	1HE08AA
HP 90W USB-C Power Adapter <b>New!</b>	2LN85AA

---

#### Introduction

HP includes a high quality AC adapter with each HP Business Notebook, HP Ultrabook, and HP Docking Station. Designed and tested to ensure optimum power support, the adapter also charges the notebook's internal battery simultaneously when connected.

As a notebook user, you may also need your adapter to be as flexible as your notebook. HP offers a variety of adapters for the many circumstance in which you may use your notebook. Whether you want something compact to carry, have a unique travel situation, or would just like another AC adapter for the office or home, HP offers an adapter for almost every computing situation.

---

#### Service and Support

The warranty period for HP Adapters is one year, part replacement. Additional support is available (North America only) seven days a week, 24 hours a day by phone as well as through online support forums.

---

#### Smart AC Adapters

The HP Smart AC Adapter is the adapter included with all HP Business Notebooks and HP Docking Stations. The Smart AC Adapter is intelligent by design because it detects and regulates the electrical current that is needed for your notebook or docking station. This unique feature helps protect your product from erratic electrical currents or a power surge. Also, although you may need a higher capacity adapter for a docking station or another notebook in the office, the Smart AC Adapter can be used with any notebook - it will adjust to the power to whatever your notebook needs.

#### Key benefits

- Add an additional adapter and always have one available in the office or at home - no need to carry it with you at all times designed to enable optimum system performance

### Technical Specifications

	<b>HP 45W Smart AC Adapter</b> (H6Y88AA)
<b>Dimensions</b>	3.77 x 1.95 x .88 in (96 x 49.5 x 22.4 mm)
<b>Weight</b>	7.09 oz (201 g)
<b>Input</b>	90 to 265 VAC
<b>Input Efficiency</b>	87% min at 115 VAC
<b>Input frequency range</b>	47 to 63 Hz
<b>Input AC current</b>	1.4 A at 90 VAC
<b>Output power</b>	45W
<b>DC output</b>	
<b>Hold-up time</b>	5 msec at 115 VAC input
<b>Output current limit</b>	8A
<b>Connector</b>	HP 4.5mm Smart Barrel
<b>Operating temperature</b>	41° to 95° F (5° to 35° C)
<b>Non-operating (storage) temperature</b>	-4° to 185° F (-20° to 85° C)
<b>Altitude</b>	0 to 10,000 ft (0 to 3,048 m)
<b>Humidity</b>	Up to 95%
<b>Storage humidity</b>	Up to 95%
<b>EMI and safety certifications</b>	Worldwide safety and EMC approvals including CE, UL, cUL, GS, Australian Electric Permit, RCM, NOM, CCC, KC, CU, S mark, BSMI, ISC, PSE, PSB, NRcan, Ukrain and SII
<b>Option kit contents</b>	HP 45W Smart AC Adapter, 4.5mm to 7.4mm power DC dongle, power cord, warranty booklet
<b>Compatibility</b>	HP Spectre 13 Pro, HP Spectre x2 Pro, HP EliteBook Folio 1040, Folio 9470m HP EliteBook 1040 G1, G2, 1020 G1, 800 G1, G2, G3 Series 700 G1, G2, G3, Series, 600 G1, G2 Series, HP Revolve 810 G1, G2, G3 Series HP Elite Tablet x2 1011 G1, HP Pro Tablet 610 G1, HP 430, 440 450 G2 Series HP 215, 240 G2, 245 G2, 250 G2, 255 G2 Notebook PCs HP ProBook 11 G1 Education G1, G2, HP Pro x2 612 G1 HP Stream 11 G1, G2 HP ProBook x2 410 G1 HP ChromeBook 11 EE, G3, G4

	<b>HP 65W Smart AC Adapter</b> (H6Y89AA)
<b>Dimensions</b>	4.17 x 1.85 x 1.1 in (106 x 47 x 28 mm)
<b>Weight</b>	0.62 lb (280 g)
<b>Input</b>	90 to 265 VAC
<b>Input Efficiency</b>	84% min at 115 VAC
<b>Input frequency range</b>	
<b>Input AC current</b>	1.7 A at 90 VAC, 0.85 A at 180 VAC



### Technical Specifications

<b>Output power</b>	65W
<b>DC output</b>	18.5V
<b>Hold-up time</b>	
<b>Output current limit</b>	<5A, Over voltage protection- 29V max automatic shutdown
<b>Connector</b>	HP 4.5mm Smart Barrel
<b>Operating temperature</b>	41° to 95° F (5° to 35° C)
<b>Non-operating (storage) temperature</b>	-4° to 185° F (-20° to 85° C)
<b>Altitude</b>	0 to 10,000 ft (0 to 3,048 m)
<b>Humidity</b>	Up to 95%
<b>Storage humidity</b>	Up to 95%
<b>EMI and safety certifications</b>	Worldwide safety and EMC approvals including CE, UL, CSA or cUL, GS, Australian Electric Permit, C-tick, NOM, CCC, KC, GOST, SABS, S mark, BSMI, ISC, PSE, PSB and SIL.
<b>Option kit contents</b>	HP 65W Smart AC Adapter, 4.5mm to 7.4mm power DC dongle, power cord, warranty booklet
<b>Compatibility</b>	HP ChromeBook 14, HP Spectre 13 Pro, HP Spectre x2 Pro, HP EliteBook Folio 1040 Notebook PCs, HP 215, 240 G2, 242 G1, 245 G2, 250 G2, 255 G2 Notebook PCs HP ProBook Notebook PCs, HP EliteBook 8XX, Folio 9470m, Revolve 810, 2XXp, 84XXp, and 85XXp Notebook PCs, HP ZBook 14, EliteBook 84XXw Mobile Workstations, HP Mini 51XX, HP 31XXm, HP 240, 246, 248, 340, 250, 255, 430, 431, 435, 436, 450, 455, 630, 631, 635, 636, 650, and 655 Notebook PCs, HP mt20, mt40, mt41, and HP ProBook 6360t Thin Clients

	<b>HP 90W Smart AC Adapter</b> (H6Y90AA)
<b>Dimensions</b>	5.00 x 1.97 x 1.1 in (127 x 50 x 29 mm)
<b>Weight</b>	0.82 lb (370 g)
<b>Input</b>	100 to 240 VAC
<b>Input Efficiency</b>	88% at 115VAC 89% at 230 VAC
<b>Input frequency range</b>	47 to 63 Hz
<b>Input AC current</b>	1.5 A at 90 VAC, 0.75 A at 180 VAC PFC Version
<b>Output power</b>	90W
<b>DC output</b>	19.0V
<b>Hold-up time</b>	5 msec at 115 VAC input
<b>Output current limit</b>	<11A, Over voltage protection- 29V max automatic shutdown
<b>Connector</b>	HP 4.5 mm Smart Barrel
	Environmental design
<b>Operating temperature</b>	32° to 104° F (0° to 40° C)
<b>Non-operating (storage) temperature</b>	-4° to 149° F (-20° to 65° C)
<b>Altitude</b>	0 to 10,000 ft (0 to 3,048 m)
<b>Humidity</b>	20% to 80%
<b>Storage humidity</b>	10% to 90%



### Technical Specifications

<b>EMI and safety certifications</b>	Worldwide safety and EMC approvals including CE, UL, CSA or cUL, GS, Australian Electric Permit, C-tick, NOM, CCC, KC, GOST, SABS, S mark, BSMI, ISC, PSE, PSB and SII.
<b>Option kit contents</b>	HP 90W Smart AC Adapter, 4.5mm to 7.4mm power DC dongle, power cord, warranty booklet
<b>Compatibility</b>	HP ChromeBook 14, HP Spectre 13 Pro, HP Spectre x2 Pro, HP EliteBook Folio 1040 Notebook PCs, HP 215, 240 G2, 242 G1, 245 G2, 250 G2, 255 G2 Notebook PCs HP ProBook Notebook PCs, HP EliteBook 8XX, 2XXXp, and 8XXXp, Folio 9470m, Revolve 810 Notebook PCs, HP ZBook 14, and EliteBook 84XXw, and 8540w Mobile Workstations, HP 31XXm, HP 240, 246, 248, 340, 250, 255, 430, 431, 435, 436, 450, 455, 630, 631, 635, 636, 650, and 655 Notebook PCs, HP mt20, mt40, mt41, HP ProBook 6360t Thin Clients

	<b>HP 150W 4.5mm Smart AC Adapter (W2F74AA)</b>
<b>Dimensions</b>	6.02 x 25 x 0.88 in (15 x 66 x 22 mm)
<b>Weight</b>	0.705 lb (320g)
<b>Input</b>	90 to 265 VAC RMS.
<b>Input Efficiency</b>	88% min at 115 VAC
<b>Input frequency range</b>	47 – 63 Hz AC.
<b>Input AC current</b>	2.7 A at 90 VAC
	<b>Output</b>
<b>Output power</b>	150W
<b>DC output</b>	19.50V +5.0%/–5%
<b>Hold-up time</b>	5 msec at 115 VAC input
<b>Output current limit</b>	<-15 A, Over voltage protection- 29V max automatic shutdown
<b>Connector</b>	HP 4.5 mm Smart Barrel
	<b>Environmental design</b>
<b>Operating temperature</b>	0 to 35°C.
<b>Non-operating (storage) temperature</b>	-20 to 85°C.
<b>Altitude</b>	Operating: The power supply can be operated at 5,000 m above sea level. Non-Operating: 50,000 feet above sea level.
<b>Humidity</b>	Up to 95%
<b>Storage humidity</b>	Up to 95%
<b>EMI and safety certifications</b>	Worldwide safety and EMC approvals including CE, UL, CSA or cUL, GS, Australian Electric Permit, C-tick, NOM, CCC, KC, GOST, SABS, S mark, BSMI, ISC, PSE, PSB and SII.
<b>Warranty</b>	1 year
<b>Option kit contents</b>	AC Power brick, Country Power cord, 4.5mm to 7.4mm power dongle, Quick Set up Guide, Warranty Notification
<b>Compatibility</b>	HP ZBook Studio G3, HP ZBook 15 G3 and HP ZBook 15u G3 mobile workstations

### Technical Specifications

	<b>HP 200W 4.5mm Smart AC Adapter</b> (W2F75AA)
<b>Dimensions</b>	6.77 x 3.77 x1 in (172 x 96 x 25.4 mm)
<b>Weight</b>	1.92 lb (875g)
<b>Input</b>	90 to 265 VAC RMS.
<b>Input Efficiency</b>	88% at 115 VAC input and 89% at 230 VAC
<b>Input frequency range</b>	47 – 63 Hz AC.
<b>Input AC current</b>	2.7 A at 90 VAC
	<b>Output</b>
<b>Output power</b>	200W
<b>DC output</b>	19.50V +5.0%/-5%
<b>Hold-up time</b>	5 msec at 115 VAC input
<b>Output current limit</b>	<-16 A, Over voltage protection- 29V max automatic shutdown
<b>Connector</b>	HP 4.5 mm Smart Barrel
	<b>Environmental design</b>
<b>Operating temperature</b>	0 to 35°C.
<b>Non-operating (storage) temperature</b>	-20 to 85°C.
<b>Altitude</b>	Operating: The power supply can be operated at 5,000 m above sea level. Non-Operating: 50,000 feet above sea level.
<b>Humidity</b>	Up to 95%
<b>Storage humidity</b>	Up to 95%
<b>EMI and safety certifications</b>	Worldwide safety and EMC approvals including CE, UL, CSA or cUL, GS, Australian Electric Permit, C-tick, NOM, CCC, KC, GOST, SABS, S mark, BSMI, ISC, PSE, PSB and SII.
<b>Warranty</b>	1 year
<b>Option kit contents</b>	AC Power brick, Country Power cord, 4.5mm to 7.4mm power dongle, Quick Set up Guide, Warranty Notification
<b>Compatibility</b>	HP ZBook 17 G3, G4

### Slim Adapters

The HP Slim AC Adapters are 40% thinner than the standard notebook adapter.

### Key benefits:

- Provides a convenient and portable power source for use in a mobile environment
- Includes a convenient USB port for charging other accessories while you work

	<b>HP 65W Slim AC Adapter</b> (H6Y82AA)
<b>Dimensions</b> w/o DC cable	4.72 x 2.28 x 0.67 in (120 x 58 x 17 mm)
<b>Weight</b>	0.49 lb (222.6 g)
<b>Input</b>	100 to 240 VAC
<b>Input efficiency</b>	83% min at 115 VAC

### Technical Specifications

<b>Input frequency range</b>	47 to 63 Hz
<b>Input AC current</b>	<1.7 A at 90 VAC
	<b>Output</b>
<b>Output power</b>	65W
<b>DC output</b>	19.50V +5.0%/-5.0%
<b>Hold-up time</b>	5 msec at 115 VAC input
<b>Output current limit</b>	<11A, Over voltage protection- 29V max automatic shutdown
<b>Connector</b>	3 pin/grounded, mates with interchangeable cords
	<b>Environmental design</b>
<b>Operating temperature</b>	32° to 104° F (0° to 40° C)
<b>Non-operating (storage) temperature</b>	-4° to 149° F (-20° to 65° C)
<b>Altitude</b>	0 to 10,000 ft (0 to 3,048 m)
<b>Humidity</b>	20% to 80%
<b>Storage humidity</b>	10% to 90%
<b>EMI and safety certifications</b>	Worldwide safety and EMC approvals including CE, UL, CSA or cUL, GS, Australian Electric Permit, C-tick, NOM, CCC, KC, GOST, SABS, S mark, BSMI, ISC, PSE, PSB and SII.
<b>Option kit contents</b>	HP Slim Adapter, DC connector tips (4.5mm/7.4mm Smart, Ultrabook™), detachable cable, AC power cord, documentation, quick setup poster and warranty
<b>Compatibility</b>	HP ChromeBook 14, HP Spectre 13 Pro, HP Spectre x2 Pro, HP EliteBook Folio 1040 Notebook PCs, HP 215, 240 G2, 242 G1, 245 G2, 250 G2, 255 G2 Notebook PCs HP ProBook Notebook PCs, HP EliteBook 8XX, Folio 9470m, Revolve 810, 2XXXp, 84XXp, and 85XXp Notebook PCs, HP ZBook 14, EliteBook 84XXw Mobile Workstations, HP Pavilion 14 Chromebook, HP Folio 13 Notebook PC, HP SpectreXT Pro Ultrabook™, HP ENVY Pro Ultrabook™, HP Mini 51XX, HP 31XXm, HP 240, 246, 248, 340, 250, 255, 430, 431, 435, 436, 450, 455, 630, 631, 635, 636, 650, and 655 Notebook PCs, HP mt20, mt40, mt41, and HP ProBook 6360t Thin Clients

	<b>HP 90W Slim AC Adapter</b> (H6Y83AA)
<b>Dimensions</b> w/o DC cable	5.43 x 2.28 x 0.67 in (138 x 58 x 17 mm)
<b>Weight</b>	0.49 lb (222.6 g)
<b>Input</b>	100 to 240 VAC
<b>Input efficiency</b>	87% min at 115 VAC
<b>Input frequency range</b>	47 to 63 Hz
<b>Input AC current</b>	<1.6 A at 90 VAC
	<b>Output</b>
<b>Output power</b>	90W
<b>DC output</b>	19.50V +5.0%/-5.0%
<b>Hold-up time</b>	5 msec at 115 VAC input
<b>Output current limit</b>	<11A, Over voltage protection- 29V max automatic shutdown
<b>Connector</b>	3 pin/grounded, mates with interchangeable cords

### Technical Specifications

	<b>Environmental design</b>
<b>Operating temperature</b>	32° to 104° F (0° to 40° C)
<b>Non-operating (storage) temperature</b>	-4° to 149° F (-20° to 65° C)
<b>Altitude</b>	0 to 10,000 ft (0 to 3,048 m)
<b>Humidity</b>	20% to 80%
<b>Storage humidity</b>	10% to 90%
<b>EMI and safety certifications</b>	Worldwide safety and EMC approvals including CE, UL, CSA or cUL, GS, Australian Electric Permit, C-tick, NOM, CCC, KC, GOST, SABS, S mark, BSMI, ISC, PSE, PSB and SII.
<b>Option kit contents</b>	HP Slim Adapter, DC connector tips (4.5mm/7.4mm Smart, Ultrabook™), detachable cable, AC power cord, documentation, quick setup poster and warranty
<b>Compatibility</b>	HP ChromeBook 14, HP Spectre 13 Pro, HP Spectre x2 Pro, HP EliteBook Folio 1040 Notebook PCs, HP 215, 240 G2, 242 G1, 245 G2, 250 G2, 255 G2 Notebook PCs HP ProBook Notebook PCs, HP EliteBook 8XX, 2XXXp, and 8XXXp, Folio 9470m, Revolve 810 Notebook PCs, HP ZBook 14, and EliteBook 84XXw, and 8540w Mobile 2Workstations, HP Pavilion 14 Chromebook, HP Folio13 Notebook PC, HP SpectreXT Pro Ultrabook™, HP ENVY Pro Ultrabook™, HP 31XXm, HP 240, 246, 248, 340, 250, 255, 430, 431, 435, 436, 450, 455, 630, 631, 635, 636, 650, and 655 Notebook PCs, HP mt20, mt40, mt41, HP ProBook 6360t Thin Clients

### HP Specialized Travel Adapter

The HP Smart Travel AC Adapter series offers the HP Smart 65W Travel AC Adapter, which is perfect for "road warriors" who are always on the go. The adapter is 40% thinner than the standard 65W adapter.

#### Key benefits:

- Provides a convenient and portable power source for use in a mobile environment
- Includes a convenient USB port for charging other accessories while you work
- Offers four international adapter plugs (U.S., EU, Japan, and UK) for usage almost anywhere in the world
- A stylish protective carrying case keeps everything together

	<b>HP 65W Smart Travel AC Adapter</b> (JOE43AA)	
<b>Dimensions</b>	4.72 x 2.28 x 0.67 in (120 x 58 x 17 mm)	
<b>Weight</b>	0.49 lb (222.6 g)	
<b>Input</b>	100 to 240 VAC	
	<b>Input efficiency</b>	83% min at 115 VAC
	<b>Input frequency range</b>	47 to 63 Hz
	<b>Input AC current</b>	1.7 A at 90 VAC, 0.85 A at 180 VAC
<b>Output</b>	<b>Output power</b>	65W
	<b>DC output</b>	19.5V 5.0V
	<b>Hold-up time</b>	5 msec at 115 VAC input
	<b>Output current limit</b>	<5A, Over voltage protection- 29V max automatic shutdown
<b>Connector</b>	3 pin/grounded, mates with interchangeable cords	

### Technical Specifications

<b>Environmental design</b>	<b>Operating temperature</b>	32° to 104° F (0° to 40° C)
	<b>Non-operating (storage) temperature</b>	-4° to 149° F (-20° to 65° C)
	<b>Altitude</b>	0 to 10,000 ft (0 to 3,048 m)
	<b>Humidity</b>	20% to 80%
	<b>Storage humidity</b>	10% to 90%
<b>EMI and safety certifications</b>	Worldwide safety and EMC approvals including CE, UL, CSA or cUL, GS, Australian Electric Permit, C-tick, NOM, CCC, KC, GOST, SABS, S mark, BSMI, ISC, PSE, PSB and SII.	
<b>Option kit contents</b>	HP Slim Adapter, DC connector tips (4.5mm/7.4mm Smart, Ultrabook™), detachable cable, AC power cord, US/Japan/EU/UK duck heads, documentation, quick setup poster, warranty, and carrying case.	
<b>Compatibility</b>	HP ChromeBook 14, HP Spectre 13 Pro, HP Spectre x2 Pro, HP EliteBook Folio 1040 Notebook PCs, HP 215, 240 G2, 242 G1, 245 G2, 250 G2, 255 G2 Notebook PCs HP ProBook Notebook PCs, HP EliteBook 8XX, Folio 9470m, Revolve 810, 2XXXp, 84XXp, and 85XXp Notebook PCs, HP ZBook 14, EliteBook 84XXw Mobile Workstations, HP Pavilion 14 Chromebook, HP Folio13 Notebook PC, HP SpectreXT Pro Ultrabook™, HP ENVY Pro Ultrabook™, HP Mini 51XX, HP 31XXm, HP 240, 246, 248, 340, 250, 255, 430, 431, 435, 436, 450, 455, 630, 631, 635, 636, 650, and 655 Notebook PCs, HP mt20, mt40, mt41, and HP ProBook 6360t Thin Clients	

### HP Combo Adapters

HP 90W Combo Adapters are designed for mobile workers who need an adapter while traveling in the car or by air.

	<b>HP 90W Slim Combo Adapter with USB detachable DC cable + tips (H6Y84AA)</b>	
<b>Dimensions</b>	5.94 x 2.75 x 1.00 in (151 x 70 x 25 mm)	
<b>Weight</b>	0.88 lb (400 g)	
<b>AC input</b>	90 to 264 VAC	
	<b>Input frequency range</b>	47 to 63 Hz
<b>DC input</b>	10 to 32 VDC	
	<b>Input DC current</b>	12.5 at 10VDC
<b>Output</b>	<b>Output power</b>	100W
	<b>DC output</b>	19.5V 5V / 2A (USB)
<b>Environmental design</b>	<b>Operating temperature</b>	32° to 95° F (0° to 35° C)
	<b>Non-operating (storage) temperature</b>	-4° to 185° F (-20° to 85° C)
	<b>Altitude</b>	0 to 19,685 ft (0 to 5,000 m)
	<b>Humidity</b>	20% to 95%
	<b>Storage humidity</b>	5% to 95%
<b>EMI and safety certifications</b>	Worldwide safety and EMC approvals including CE, UL, CSA or cUL, GS, Australian Electric Permit, C-tick, NOM, CCC, KC, GOST, SABS, S mark, BSMI, ISC, PSE, PSB and SII.	





### Technical Specifications

<b>Option kit contents</b>	HP 90W Slim Combo Adapter, DC connector tips (4.5mm/7.4mm Smart, Ultrabook™), detachable DC cable, AC power cord, auto/truck cigarette lighter cable, replacement fuses, quick setup poster, warranty, and carrying case.
<b>Compatibility</b>	HP ChromeBook 14, HP Spectre 13 Pro, HP Spectre x2 Pro, HP EliteBook Folio 1040 Notebook PCs, HP 215, 240 G2, 242 G1, 245 G2, 250 G2, 255 G2 Notebook PCs HP ProBook Notebook PCs, HP EliteBook 8XX, 2XXXp, and 8XXXp, Folio 9470m, Revolve 810 Notebook PCs, HP EliteBook Mobile Workstations, HP Pavilion 14 Chromebook, HP Folio13 Notebook PC, HP SpectreXT Pro Ultrabook™, HP ENVY Pro Ultrabook™, HP 31XXm, HP 240, 246, 248, 340, 250, 255, 430, 431, 435, 436, 450, 455, 630, 631, 635, 636, 650, and 655 Notebook PCs, HP mt20, mt40, mt41, HP ProBook 6360t Thin Clients

### HP USB-C Power Adapter

Power and charge your notebook or tablet<sup>1</sup> from its USB-C™ port with the HP USB-C™ AC Adapter. Connect one end of the adapter to the USB-C™ port on your device<sup>1</sup>, and plug the AC head into any available wall outlet.

Get a one-year limited warranty.

[USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum.](#)

		<b>HP 45W USB-C Power Adapter (V5Y26AA)</b>
<b>Dimensions</b>	66mm x 66mm mm x 28.5 mm	
	<b>Input Efficiency</b>	78.71% min at 115V/230V(option) @5V/2A 87.41% min at 115V/230V(option) @12V/3A 87.73% min at 115V/230V(option) @15V/3A
	<b>Input frequency range</b>	47 to 63 Hz
	<b>Input AC current</b>	1.4 A at 90 VAC and maximum load
<b>Output</b>	<b>Output power</b>	45W max
	<b>DC output</b>	5V/12V/15V
	<b>Hold-up time</b>	5msec at 115 VAC input
	<b>Output current limit</b>	< 5A Over voltage protection: 5V less than 7.25V 12V less than 16.85V 15V less than 20.5V
<b>Connector</b>	3 pin/grounded, mates with type-C connector	
<b>Environmental Design</b>	<b>Operating temperature</b>	0° to 35° C
	<b>Non-operating (storage) temperature</b>	-20° to 85° C
	<b>Altitude</b>	0 to 5,000 m
	<b>Humidity</b>	0% to 95%

### Technical Specifications

	<b>Storage Humidity</b>	0% to 95%
<b>Safety Certifications</b>	CE Mark - EMC directives; Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE; Reliability - failure rate of less than 0.1% annually within the first three years of operation.	
<b>Compatibility</b>	HP x2 1012 G1 Tablet, HP EliteBook 1030 G1	

	<b>HP 45 USB-C G2 Power Adapter (1HE07AA)</b>	
<b>Dimensions</b>	62 x 62 x 28.5 mm	
<b>Weight</b>	220g +/- 10g	
	<b>Input Efficiency</b>	Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec: 5V : 81.5% 9V : 86.7% 10V : 87.5% 12V : 87.8% 15V : 87.8% 20V : 87.8%
	<b>Input frequency range</b>	47 ~ 63Hz
	<b>Input AC current</b>	Max. 1.4 A at 90 Vac
<b>Output</b>	<b>Output power</b>	5V/15W 9V/27W 10V/37.5W 12V/45W 15V/45W 20V/45W
	<b>DC output</b>	5V / 9V / 10V / 12V / 15V / 20V
	<b>Hold-up time</b>	5ms at 115 Vac input
	<b>Output current limit</b>	<5 A
<b>Connector</b>	USB Type-C™	
<b>Environmental Design</b>	<b>Operating temperature</b>	32°F to 95°F (0°to 35°C)
	<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20°to 85°C)
	<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
	<b>Humidity</b>	20% to 95%
	<b>Storage Humidity</b>	10% to 95%
<b>Safety Certifications</b>	Eg: *CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals –	

### Technical Specifications

	C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.
<b>Compatibility</b>	HP Spectre Pro 13 G1 Notebook PC, HP EliteBook Folio G1, HP x2 612 G2 Tablet, HP x2 1012 G1 Tablet

	<b>HP 45W USB-C LC Power Adapter (1MZ01AA)</b>	
<b>Dimensions</b>	94 x 40 x 26.5 mm	
<b>Weight</b>	192.5g +/-10%	
	<b>Input Efficiency</b>	Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec: 5V : 78.71% 12V : 87.41% 15V : 87.73%
	<b>Input frequency range</b>	47 ~ 63Hz
	<b>Input AC current</b>	Max. 1.4 A at 90 Vac
<b>Output</b>	<b>Output power</b>	5V/10W 12V/36W 15V/45W
	<b>DC output</b>	5V/12V/15V
	<b>Hold-up time</b>	5ms at 115 Vac input
	<b>Output current limit</b>	<5 A
<b>Connector</b>	USB Type-C™	
<b>Environmental Design</b>	<b>Operating temperature</b>	32°F to 95°F (0°C to 35°C)
	<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20°C to 85°C)
	<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
	<b>Humidity</b>	20% to 95%
	<b>Storage Humidity</b>	10% to 95%
<b>Safety Certifications</b>	Eg: *CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.	
<b>Compatibility</b>	HP ChromeBook x360 11 G1 EE, HP ChromeBook 13 G1	

	<b>HP 65W USB-C Power adapter (1HE08AA)</b>	
<b>Dimensions</b>	74 x 74 x 28.5 mm	
<b>Weight</b>	245g +/- 10g	

### Technical Specifications

	<b>Input Efficiency</b>	81.5% min at 115 Vac/ 230Vac @ 5V/3A 86.7% min at 115 Vac/ 230Vac @ 9V/3A 88% min at 115 Vac/ 230Vac @ 10V/5A 88% min at 115 Vac/ 230Vac @ 12V/5A 89% min at 115 Vac/ 230Vac @ 15V/4.33A 89% min at 115 Vac/ 230Vac @ 20V/3.25A
	<b>Input frequency range</b>	47 ~ 63Hz
	<b>Input AC current</b>	1.7 A at 90 VAC and maximum load
<b>Output</b>	<b>Output power</b>	65W
	<b>DC output</b>	5V/9V/10V/12V/15V/20V
	<b>Hold-up time</b>	5ms at 115 Vac input
	<b>Output current limit</b>	<8 A
<b>Connector</b>		USB Type-C™
<b>Environmental Design</b>	<b>Operating temperature</b>	32°F to 95°F (0°to 35°C)
	<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20°to 85°C)
	<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
	<b>Humidity</b>	5% to 95%
	<b>Storage Humidity</b>	5% to 95%
<b>Safety Certifications</b>	Eg: *CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. * MTBF - over 100,000 hours at 25°C ambient condition.	
<b>Compatibility</b>	HP EliteBook x360 1020 G2, HP EliteBook 1040 G4, HP Elitebook x360, HP x2 1012 G2 Tablet, HP x2 612 G2 Tablet	

	<b>HP 90W USB-C Power Adapter (2LN85AA)</b>	
<b>Dimensions</b>	129.5x65.5x28.5mm	
<b>Weight</b>	320g	
	<b>Input Efficiency</b>	Average Efficiency of 25%, 50%, 75%, 100% load condition with 115Vac/230Vac Spec: 5V : 81.5% 9V : 86.7% 10V : 88% 12V : 88% 15V : 89% 20V : 89%
	<b>Input frequency range</b>	47 to 63 Hz
	<b>Input AC current</b>	Max. 1.8 A at 90 Vac
<b>Output</b>	<b>Output power</b>	5V/15W



### Technical Specifications

		9V/27W 10V/50W 12V/60W 15V/75W 20V/90W
	<b>DC output</b>	5V / 9V / 10V /12V / 15V / 20V
	<b>Hold-up time</b>	5msec at 115 VAC input
	<b>Output Over Current Protection</b>	<5.0A
	<b>DC Plug</b>	USB Type-C
<b>Environmental Design</b>	<b>Operating temperature</b>	32°F to 95° F (0°C to 35° C)
	<b>Non-operating (storage) temperature</b>	-4°F to 185° F (-20° to 85° C)
	<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
	<b>Humidity</b>	20% to 95%
	<b>Storage Humidity</b>	10% to 95%
<b>AMI and Safety Certifications</b>	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. MTBF - over 200,000 hours at 25°C ambient condition.	
<b>Compatibility</b>	HP EliteBook 1040 G4	

### Summary of Changes

<b>Date of change:</b>	<b>Version 1 to 2</b>		<b>Description of change:</b>
July 16, 2014	From v30 to v31	Changed	Version number to match PB/Concentra
November 11, 2014	From v31 to v32	Added	HP 15W mUSB Power Adapter
December 4, 2014	From v32 to v33	Added	Specs for the HP 15W mUSB Power Adapter and removed products no longer offered.
February 8, 2016	From v33 to v34	Updated	Compatibility for the 45W Smart AC Power adapter (H6Y88AA)
February 29, 2016	From v34 to v35	Added	HP 150W Smart AC Adapter (4.5mm) HP 200W Smart AC Adapter (4.5mm)
March 8, 2016	From v35 to v36	Added	HP 45W USB-C™ AC Adapter
		Deleted	HP 40W Smart AC Adapter HP 90W Smart Auto Adapter HP 90W Slim Combo Adapter with USB HP 230W Smart AC Adapter
July 15, 2016	From v36 to v37	Changed	Specs for HP 90W Smart AC Adapter (4.5mm) H6Y90AA
August 11, 2016	From v37 to v38	Changed	Altitude specs HP 150W Smart AC Adapter (4.5mm)
April 7, 2017	From v38 to v39	Added	HP 45 USB-C G2 Power Adapter HP 65W USB-C Power adapter HP 45W USB-C LC Power Adapter
August 3, 2017	From V39 to V40	Deleted	HP 65W Smart AC Adapter (ED494AA)
August 16, 2017	From V40 to V41	Added	HP 90W USB-C Power Adapter (2LN85AA)
April 25, 2018	From V41 to V42	Added	Weight specs to HP 90W USB-C Power Adapter

© Copyright 2018 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Ultrabook is a trademark of Intel Corporation in the U.S. and other countries. USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum.