

# NEC Collaboration powered by ThinkHub

Discover the powerful collaboration solution that is transforming the way people communicate. NEC Collaboration powered by ThinkHub is a multitouch collaboration tool that consolidates all the moving pieces of a working session: the 4K screen, devices, applications, ideas, and content that are critical to achieving great work. NEC Collaboration powered by ThinkHub is a software-based solution that has the power to replace all the hardware that we associate with collaboration systems today.

Access and annotate anything on the ThinkHub Canvas - including 4K images, videos, documents, and presentations - from a USB, network or cloud drive. Create Notes and Sketches, and access web apps and content via the built-in Multitouch Web Browser. Connect and share an unlimited number of device screens to the ThinkHub Canvas via T1V's AirConnect™ app - which supports Mac OS, iOS, Windows, Android, and Linux devices, and also allows you to control the device from the ThinkHub Canvas itself via TouchControl™ technology.

ThinkHub works with the same devices, content and software that you already use - meaning set-up time to initiate ThinkHub Sessions, and more efficient and productive workflows for your team.



MODEL	V554-THS	E705-THS	E805-THS	X651UHD-2-PREM	X841UHD-2-PREM
<b>TARGET APPLICATIONS</b>					
Room Types	Conference Rooms   Classrooms   Board Rooms   Training Rooms   Demo Centers   Huddle Spaces   Libraries   Executive Offices				
Room Size	Small to Large (3-25+ people)				
<b>LCD MODULE</b>					
Panel Technology	A-MVA	UV2A	UV2A	S-IPS	
Viewable Image Size	55"	70"	80"	65"	84"
Native Resolution	1920 X 1080			3840 x 2160	
Brightness (Typical/Max)	320 cd/m <sup>2</sup> / 450 cd/m <sup>2</sup>	360/450 cd/m <sup>2</sup>	230/460 cd/m <sup>2</sup>	320 cd/m <sup>2</sup> / 450 cd/m <sup>2</sup>	380 cd/m <sup>2</sup> / 500 cd/m <sup>2</sup>
Contrast Ratio (Typical)	4000:1	4000:1	5000:1	1300:1	1400:1
Viewing Angle	178° Vert., 178° Hor. (89U/89D/89U/89R) @ CR>10				
Aspect Ratio	16:9				
Active Screen Area (W x H)	56.2 x 31.6 in. / 1428.5 x 803.5 mm	60.6 x 34.1 in. / 1538.9 x 865.6 mm	69.7 x 39.2 in. / 1771.2 x 996.3 mm	56.3 x 31.6 in. / 1428.48 x 803.52 mm	73.7 x 41.6 in. / 1871.0 x 1057 mm
Displayable Colors	Greater than 1.07 Billion		Greater than 1.07 Billion		
Orientation	Landscape/Portrait				
<b>CONNECTIVITY</b>					
Input Terminals	Digital	DisplayPort (with HDCP), HDMI (with HDCP), DVI-D (Dual-Link with HDCP)	DisplayPort, HDMI x2, DVI	DisplayPort (with HDCP), HDMI (with HDCP), DVI-D (Dual-Link with HDCP)	DisplayPort 1.2; DVI-D (1), HDMI (4)
	Audio	Stereo Mini-Jack, DisplayPort Audio, HDMI Audio	Audio Mini-Jack x2	Audio Mini-Jack, DisplayPort Audio, HDMI Audio (4)	
	External Control	RS-232C, LAN, IR Remote In Audio Mini-Jack	Ethernet (RJ45), RS-232C	RS-232C, LAN, DDC/CI RS-232C, LAN, DDC/CI	IR remote in RS-232C, LAN, USB Upstream/Downstream
Output Terminals	Audio	Stereo Mini-Jack, External Speaker Jack (2)	Audio Mini-Jack, External Speaker Jack x2	Audio Mini-Jack	
	Speakers	Integrated (10W x 2)			
	External Control	RS-232C			LAN
<b>POWER CONSUMPTION</b>					
On (Typical)	100W	150W	230W	150W	380W
Auto Power Save	<2W	<2.5W			
<b>PHYSICAL SPECIFICATIONS</b>					
Bezel Width (L/R, T/B)	0.7 in./0.7 in., 0.7 in./0.7 in.; 18.3mm/18.3mm, 18.3mm/18.3mm	0.9/0.9, 0.9/0.9 in. / 23.0/23.0, 23.0/23.0 mm	1.2/1.2, 1.2/1.2 in. / 29.7/29.7, 29.7/29.7mm	0.69 in. / 0.69 in., 0.69 in. / 0.69 in.; 17.5mm/17.5mm, 17.5mm/17.5mm	1.3 in./1.3 in., 1.3in/1.3in.; 32.6mm/32.6mm, 32.6mm/32.6mm
Net Dimensions (without stand; WxHxD)	49.2 x 28.4 x 2.5 in. / 1249.7 x 720.5 x 63mm	62.5 x 36.2 x 3.4 in. / 1587.0 x 919.6 x 86.9 mm	72.3 x 41.8 x 3.4 in. / 1836.2 x 1061.3 x 86.9mm	58.0 x 33.4 x 3.3 in. / 1472.4 x 847.6 x 84.4mm	76 x 44 x 3.3 in. / 1931 x 1117 x 85mm
Net Weight (without stand)	58 lbs. / 26.3 kg	103.4lbs / 47.0 kg	132.3lbs / 60 kg	92.6lbs. / 42.0kg	155.4 lbs. / 70.5 kg
VESA Hole Configuration	400 x 400mm (4-hole)				
<b>ENVIRONMENTAL CONDITIONS</b>					
Operating Temperature	41-104°F / 5-40°C			32-104°F / 0-40°C	
Operating Humidity	20 - 80%				
Operating Altitude	9843 ft. / 3000m				
LIMITED WARRANTY	3 years parts and labor, including backlight*				
<b>THINKHUB DEVICE</b>					
Dimensions (W x H x D)	7.7 in x 1.4 in x 7.7 in / 19.7 cm x 3.6cm 19.7 cm			6.6 in x 9.9 in x 6.6 in / 16.76 x 5.15 cm x 16.76 cm	
Weight	2.6 lbs			11 lbs	
Storage / RAM	1TB / 8GB			256 GB	
Processor	2.6GHz dual-core Intel Core i5			Intel Xeon E5 3.7GHz quad-core	
Graphics	Intel Iris Graphics			Dual AMD FirePro D300	
Network	Wired 1Gbps Optional WiFi 802.11ac/802.11 a/b/g/n				
Built-in Protocol	AirPlay and T1V AirConnect				
I/O	(4) USB 3.0, (1) Ethernet 1000 Base-T, (2) MiniDisplayPort Video Output, (1) HDMI Video Output*, 3.5mm Stereo Out, 3.5mm Stereo In			(4) USB 3.0, (1) Dual Gigabit Ethernet, (6) Thunderbolt 2, HDMI 1.4 Ultra HD	
*ThinkHub will display 2 inputs at a time.					
Hardware Warranty	3 year				
<b>BYOD CONNECTIVITY</b>					
MultiSite	Real time interaction with up to 10 locations, with 1 live stream (all other streams are snapshots)				
Video conferencing	AirConnect™, Skype for Business Integration *additional fees may apply				
Hardline inputs	Up to 4 (optional add on; additional fees may apply)				
AirPlay	Supports unlimited number of devices on Mac / iOS Platforms				
Recommended bandwidth per live stream	typical: 300 kb/s   max: 11 mb/s				
Streaming Media	Stream 1080p at 30fps w/synchronized audio (iOS)				
T1V AirConnect App	Supports unlimited number of devices and 2 livestream devices on Mac, iOS, Windows, Android, Linux Platforms				
Recommended bandwidth per live stream	typical: 300 kb/s   max: 3 mb/s				
Streaming Media	Stream 1080p at 30fps w/synchronized audio (Mac OS, Windows)				
Wireless Device Connectivity	No dongle needed; toggle between users via App				
Network Modes	Direct Mode: Compatible with a single subnet and or multiple subnets				

Visit [www.necdisplay.com/collaboration](http://www.necdisplay.com/collaboration) to learn more.

Contact Info:  
 Phone: 866.NEC.MORE, 1, 4380  
 Email: [thinkhub@necdisplay.com](mailto:thinkhub@necdisplay.com)

All rights reserved in favor of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 2016 NEC Display Solutions of America, Inc. All rights reserved.

\*Product warranty, if any, is provided directly by the manufacturer of the product. Warranty periods and warranty terms and conditions are as specified by each manufacturer in their applicable warranty statement. NEC does not provide any warranty on third party (non-NEC manufactured) products.