

# EB-530



## DATASHEET



The EB-530 delivers superior-quality images and a host of additional features as standard to give users more for their money. Ideal for classrooms or small meeting rooms, this projector can be wall or ceiling mounted or placed on a table close to the wall to free-up more workspace.

### High-quality image

Complete with our 3LCD technology, the EB-530 displays superior-quality, bright images with more accurate colours. The image can be seen even in brightly-lit rooms thanks to an equally high white and colour light output. Image detail is clear thanks to a high contrast ratio and our new short throw lens means sharper images and improved focus.

### More value for your money

The lamp in the EB-530 now lasts up to 10,000 hours in eco mode. The projector even conserves power during presentations by automatically adjusting the light output depending on the content. The A/V mute function pauses the presentation and dims the lamp by 70% to conserve energy while the projector is not in use. The projectors' built-in 16w speaker means audio content can be played directly through the projector, without the need for additional external speakers. The microphone input transforms the projector into a PA system, meaning presenters can be easily heard in a classroom environment.

### Easy to set up and use

The EB-530 has both horizontal and vertical keystone correction to achieve a perfectly shaped image and help avoid distortion. When setting up several projectors, the OSD settings can be copied from one projector to many others meaning you don't need to set up projectors individually. Multi-PC projection software allows content from four devices, including PC's, tablets, smart phones, to be displayed simulatenously.

## KEY FEATURES

- **Exceptional image quality**  
Epson's 3LCD technology displays brighter images and more accurate colours
- **Equally high white and colour light output**  
Projected image can be seen clearly even in brightly-lit rooms
- **Clearer detail**  
Increased contrast ratio of 16,000:1
- **Longer lamp life means low TCO**  
10,000 hours in eco mode / 5,000 hours in normal mode
- **Flexible installation options**  
Horizontal and vertical keystone correction for off-centre and uneven placement



**EPSON**<sup>®</sup>  
EXCEED YOUR VISION

## PRODUCT SPECIFICATIONS

|                          |   |
|--------------------------|---|
| <b>TECHNOLOGY</b>        |   |
| Projection System        | 3LCD Technology   |
| LCD Panel                | 0.55 inch with MLA (D8)   |
| <b>IMAGE</b>             |   |
| Colour Light Output      | 3,200 lumen-1,800 lumen (economy)   |
| White Light Output       | 3,200 lumen - 1,800 lumen (economy) In accordance with ISO 21118:2012   |
| Resolution               | XGA, 1024 x 768, 4:3  |
| Contrast Ratio           | 16,000 : 1  |
| Lamp                     | 215 W, 5,000 h durability, 10,000 h durability (economy mode)   |
| Keystone Correction      | Manual vertical: $\pm 15^\circ$ , Manual horizontal $\pm 15^\circ$  |
| Colour Reproduction      | Upto 1.07 billion colours   |
| <b>OPTICAL</b>           |   |
| Projection Ratio         | 0.55:1  |
| Zoom                     | Digital, Factor: 1 - 1.35   |
| Projection Size          | 50 inches - 108 inches  |
| Projection Distance Wide | 0.5 m (50 inch screen)  |
| Projection Distance Tele | 1.3 m (108 inch screen)   |
| Projection Lens F Number | 1.6   |
| Focal Distance           | 6.4 mm  |
| Focus                    | Manual  |
| Offset                   | 9.51 : 1  |
| <b>CONNECTIVITY</b>      |   |
| USB Display Function     | 3 in 1: Image / Mouse / Sound   |
| Interfaces               | Cinch audio in, Microphone input, Stereo mini jack audio in (2x), Stereo mini jack audio out, S-Video in, Component in (2x), Composite in, HDMI in, VGA out, VGA in (2x), Wireless LAN IEEE 802.11b/g/n (optional), Ethernet interface (100 Base-TX / 10 Base-T), RS-232C, USB 2.0 Type B, USB 2.0 Type A |
| Epson iProjection App    | Ad-Hoc / Infrastructure   |
| <b>ADVANCED FEATURES</b> |   |
| Security                 | Kensington lock, Security bar, Wireless LAN unit lock, Wireless LAN security, Password protection   |
| Features                 | Built-in speaker, Customizable user logo, Digital zoom, Dynamic lamp control, Horizontal and vertical keystone correction, Long lamp life, Microphone input, Wireless LAN capable   |
| Video Colour Modes       | Blackboard, Dynamic, Presentation, sRGB, Theatre  |
| <b>GENERAL</b>           |   |
| Energy Use               | 298 W, 221 W (economy), 0.28 W (standby)  |
| Product dimensions       | 344 x 315 x 94 mm (Width x Depth x Height)  |
| Product weight           | 3.7 kg  |
| <b>OTHER</b>             |   |
| Warranty                 | 24 months Carry in, Lamp: 12 months or 1,000 h<br>Optional warranty extension available   |

## LOGISTICS INFORMATION

|                          |                    |
|--------------------------|--------------------|
| SKU                      | V11H673041         |
| EAN code                 | 8715946541495      |
| Dimensions Single Carton | 504 x 386 x 209 mm |
| Carton Weight            | 5.6 Kg             |
| Multiple Order Quantity  | 1 Units            |
| Country of Origin        | China              |



For more information please contact:

Telephone: 01952 607111 (UK)+  
01 436 7742 (Republic of Ireland)  
E-mail: [enquiries@epson.co.uk](mailto:enquiries@epson.co.uk)  
Chat: [etalk.epson-europe.com](https://etalk.epson-europe.com)  
Fax: 0871 222 6740  
+ Local call rate.

Web: [www.epson.co.uk](http://www.epson.co.uk)  
[www.epson.ie](http://www.epson.ie)

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.  
Product information is subject to change without prior notice.

## EB-530

### WHAT'S IN THE BOX

- User manual (CD)
- Software (CD)
- Setup guide
- Remote control incl. batteries
- Power cable
- Main unit
- Computer cable

### OPTIONAL ACCESSORIES

- Control and Connection Box - ELPCB02 [240v]  
V12H614040DA
- Ceiling Mount - ELPMB23 - White  
V12H003B23
- Ceiling pipe - ELPP13 - 668-918mm  
V12H003P13
- Ceiling pipe - ELPP14 - 918-1168mm  
V12H003P14
- Quick Wireless Connect USB key - ELPAP09  
V12H005M09
- Air Filter - ELPAF47 - EB-52x / EB-53x  
V13H134A47
- Lamp - ELPLP87 - EB-52x / 53x (215W)  
V13H010L87
- Wall Mount - ELPMB45 - ST EB52x/53x  
V12H706040
- ELPSP02 - Active speakers  
V12H467040DA

**EPSON**<sup>®</sup>