

## DS-2CD2D14WD/M



### Key Features

- Up to 1.0 megapixel (1280 × 720 @ 30 fps) resolution
- Standard video compression with high compression ratio, ROI (region of interest) encoding
- 100 dB Wide Dynamic Range, suitable for strong backlight environment
- Progressive scan CMOS
- IR cut filter with auto switch
- 3D Digital Noise Reduction
- Support dual stream, and the sub-stream for mobile surveillance
- Support Rotate Mode, Backlight Compensation and Auto-electronic shutter, etc
- Mini design
- Other functions: heartbeat, mirror, watermark, etc
- Support intrusion detection and line crossing detection
- Support VCA, which is compatible with NVR for the second time of video searching and analysing

### Application Scenarios:

It is suitable for lift, ATM or vehicle where need hidden surveillance.

### Specifications:

Model	DS-2CD2D14WD/M
parameters	1.0 Megapixel CMOS WDR Mini Network Camera
<b>Camera</b>	
Image Sensor	1/4" Progressive Scan CMOS
Min. Illumination	0.01Lux @(F1.2,AGC ON) ,0 Lux with IR 0.028Lux @(F2.0,AGC ON) ,0 Lux with IR
Shutter Speed	1/3 s to 1/100,000 s
Lens	2.8mm@F2.0, Angle of view: 67.3°; 4mm@F2.0, Angle of view: 53°
Lens Mount	M12

Day &Night	IR cut filter with auto switch
Wide Dynamic Range	100 dB
Digital Noise Reduction	3D DNR
<b>Compression Standard</b>	
Video Compression	H.264 / MJPEG
H.264 encoding level	Main Profile
Video Bit Rate	32Kbps~8Mbps
<b>Image</b>	
Max. Resolution	1280 × 720
Frame Rate	50 Hz: 25 fps (1280 x 720), 25 fps (704 x 576), 25 fps (640 x 480) 60 Hz: 30 fps (1280 x 720), 30 fps (704 x 576), 30 fps (640 x 480)
Image Settings	Saturation, Brightness, Contrast adjustable by client software or web browser
Backlight compensation	Yes, zone optional
ROI	Support
<b>Network</b>	
Network Storage	NAS (Support NFS, SMB/CIFS)
Alarm Trigger	Motion detection, Dynamic analysis, Tampering alarm, Network disconnect , IP address conflict, Storage exception
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP, PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6,Bonjour
General	One-key reset, Flash-prevention, dual stream, heartbeat, mirror, password protection, privacy mask, watermark, IP address filtering, Anonymous access
Standard	ONVIF, PSIA, CGI, ISAPI
<b>Interface</b>	
Communication Interface	1 RJ45 10M/100M Ethernet interface
<b>General</b>	
Operating Conditions	-30 °C – 60 °C (-22 °F – 140 °F) Humidity 95% or less (non-condensing)
Power Supply	12VDC±10%
Power Consumption	3W MAX
Dimensions (mm)	37.3×41.4×24.3
Weight	55g(0.12lbs)

## Order Models

DS-2CD2D14WD/M

## Dimensions

