



43" Professional Digital Signage display with an 18/7 operating time and a 4K UHD resolution

See the difference with the ProLite LE4340UHS. A professional digital signage display with 4K graphics, 18/7 operating time and landscape orientation. Featuring a slim bezel, an AMVA3 LED panel for exceptional color and image performance and iiSignage, iiyama's free signage content creation and management software, the LE4340UHS offers businesses an easy and effective solution to help capture their audience's attention.

Also available in 55 inch: [LE5540UHS-B1](#), 65 inch: [LE6540UHS-B1](#), 75 inch: [LE7540UHS-B1](#) and 86 inch: [LE8640UHS-B1](#)



iiSignage

With iiSignage, you can easily create, publish and manage your own digital signage content on any iiyama 40-series display from a desktop PC in the same network. Use rich content like video's and widgets to create highly impactful advertising in minutes and schedule your content across multiple displays to best match your customers' behavior.



4K

UHD resolution (3840x2160), better known as 4K, offers a gigantic viewable area with 4 times more information and work space than a Full HD screen. Due to the high DPI (dots per inch), it displays an incredibly sharp and crisp image.

01 DISPLAY CHARACTERISTICS

| | |
|----------------------------------|---|
| Design | Thin bezel |
| Diagonal | 42.5" |
| Panel | AMVA3 LED, matte finish |
| Native resolution | 3840 x 2160 (8.3 megapixel 4K UHD) |
| Aspect ratio | 16:9 |
| Brightness | 350 cd/m ² typical |
| Static contrast | 5000:1 typical |
| Response time | 8ms |
| Viewing zone | horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89° |
| Colour support | 1.07B (8 bit + A-FRC) |
| Bezel width (sides, top, bottom) | 11.9mm, 11.9mm, 14.9mm |
| Bezel colour and finish | black, matte |

02 INTERFACES / CONNECTORS / CONTROLS

| | |
|------------------------|------------------------------------|
| Analog signal input | VGA x1 |
| Digital signal input | DVI x1 HDMI x2 |
| Audio input | Mini jack x1 |
| Monitor control input | RS232 x1 RJ45 (LAN) x1 IR x1 |
| Audio output | RCA (L/R) x1 Speakers 2 x 10W |
| Monitor control output | RS232 x1 IR loop through x1 |
| HDCP | yes |
| USB ports | x1 |

03 FEATURES

| | |
|------------------------------|-----------------------|
| Max. non-stop operating time | 18/7 |
| Anti image retention | yes |
| Media playback | yes |
| Housing (bezel) | plastic |
| Integrated software | Android OS, iiSignage |

04 GENERAL

| | |
|-----------------|---|
| OSD languages | EN, DE, FR, ES, IT, CN, RU, JP, CZ, NL, PL |
| Control buttons | Power, Mute, Input, Plus, Minus, Up, Down, Menu |
| Plug&Play | DDC2B, Mac OSX |

05 MECHANICAL

| | |
|----------------|-------------|
| Orientation | landscape |
| Fanless design | yes |
| VESA mounting | 400 x 400mm |

06 ACCESSORIES INCLUDED

| | |
|----------------|---------------------------------|
| Cables | power, DVI, HDMI, RS232 |
| Guides | quick start guide, safety guide |
| Remote control | yes (batteries included) |

07 POWER MANAGEMENT

| | |
|-------------------|------------------------|
| Power supply unit | internal |
| Power supply | AC 100 - 240V, 50/60Hz |

08 SUSTAINABILITY

| | |
|-------------------------|------------------------|
| Regulations | CB, CE, TÜV-Bauart, CU |
| Energy efficiency class | C |

09 DIMENSIONS / WEIGHT

| | |
|------------------------------|------------------------|
| Product dimensions W x H x D | 968.2 x 559.4 x 60.9mm |
| EAN code | 4948570116317 |

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED