

# IN2128HDx

InFocus

Bright HD Projector with Flexible Connectivity

Part #: IN2128HDx

Leverage the high brightness, networking and optional wireless device casting of the InFocus IN2128HDx projector to increase the effectiveness, visibility and sharpness of your presentations and lessons.

## Key Features

- ◆ Full HD (1920 x 1080) native resolution
- ◆ 4,000 lumens of brightness
- ◆ Network connectivity for easy management
- ◆ Display over HDMI or VGA
- ◆ PC-less display from USB drive or 4GB of internal memory
- ◆ Add the [LightCast Key](#) to wirelessly cast from any device or view documents
- ◆ 15,000:1 contrast ratio
- ◆ Powerful 10-watt speaker
- ◆ Assignable audio for connectivity options
- ◆ Blu-ray 3D capable (over HDMI)



## Connection Flexibility

This feature-packed projector offers multiple connection options. Use HDMI and VGA inputs or the on-board file viewer to present photos, PowerPoint presentations, spreadsheets, PDFs, audio, video, and more; or present directly from a USB thumb drive. Make the IT team's job easier and connect the projector to your internal network for easy remote management, or sync it with your Crestron or AMX system.



## LightCast Wireless Collaboration

Use the [LightCast Key](#) (sold separately) to easily connect and share content from your Apple, Windows, Android, or Chrome devices. Access the document viewer for PC-less presentation, and then browse the internet or use a digital whiteboard, all without connecting a device.\*

\* Wireless keyboard and mouse are recommended for digital whiteboard and internet browser usage.

captioning capabilities ensure everyone can learn and understand more clearly.

## High Brightness and Contrast

The image quality of the IN2128HDx will not disappoint. 4,000 lumens give you bright, clear images with the lights on and the high 15,000:1 contrast ratio adds sharpness with darker blacks and whiter whites.

## Sound That Fills the Room

Big sound meets big images with a 10-watt speaker that ensure your audience doesn't miss a moment. Assign audio to mix and match sound with data and video sources, plus closed



## Specifications\*

Projector	IN2128HDx
Resolution – Native	Full HD (1920 x 1080)
Display Technology	DLP
Resolution – Compatibility	VGA, WVGA, SVGA, WSVGA, XGA, WXGA, SXGA, UXGA, WSXGA+, WUXGA, WXGA+
Video Standard Compatibility	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, 480i, 480p, 576i, 720p, 1080i, 1080p
Speakers	Mono 10W x 1
Lamp Brightness	4,000 lumens
Lamp Brightness – Low Power	3,160 lumens
Lamp Life	2,000 hours
Lamp Life – Low Power	5,000 hours
Lamp Power	260W
Lamp Power – Eco Mode	65W
Replacement Lamp	SP-LAMP-094
Contrast Ratio	15,000:1
Color Wheel	6 segments, 2 vitesses
Number of Colors	1.07 billion
Aspect Ratio	16:9
Aspect Ratio Compatibility	4:3, 16:10
Lens Type	Manual focus
Projection Offset	15
Keystone Correction	± 40°V
Connectors – Inputs	3.5mm stereo audio x2, HDMI 1.4 (rear), Composite video, S-video, VGA x2
Connectors – Outputs	3.5mm audio output, Monitor out (VGA)
Audible Noise	< 34 dBA at 0°F / -17.8°C
Audible Noise – Eco Mode	< 32 dBA at 0°F / -17.8°C
Included Accessories	Power cord, Remote, VGA cable, Documentation
3D Support	720p @ 120Hz, 1080p @ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required
Product Warranty	2 years
Lamp Warranty	6 months
Accessories Warranty	90 days
Storage	4 GB
PC-less Compatibility	USB HID mouse and keyboard, USB 2.0 Type-A x2, File viewer/player, Bluetooth 4.0, USB drives, LightCast Key ready

<b>Projector</b>	<b>IN2128HDx</b>
Video Player Compatibility	AVI, 3GP, MP4, MPEG-1 (MPG, MPEG), QuickTime (MOV, QT), RealMedia (RM, RMVB)
Photo Viewer Compatibility	JPEG and JPG, PNG, Bitmap (BMP)
Music Player Compatibility	MP3, WMA, AAC, WAV
Power Standard	AC 100 to 240V, 50/60
Operating Conditions	32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m
Menu Languages	English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Romanian, Hungarian
Security Features	User PIN, Security bar, Security lock slot
Approvals	UL and c-UL, FCC, CE, CCC+CECP, KCC, NOM, PCT/CU/EAC, PSB, SABS, SASO, CB, Nemco/GS, KC
<b>Throw and Zoom</b>	
Throw Ratio – Minimum	1.15:1
Throw Ratio – Maximum	1.50:1
Zoom Ratio	1.3:1
<b>Shipping</b>	
Product Dimensions	3.9 x 11.5 x 8.7 in / 99.1 x 292.1 x 221 mm
Product Weight	5.1 lbs / 2.3 kg
Shipping Dimensions	7.8 x 14.3 x 12 in / 196.9 x 362 x 304.8 mm
Shipping Weight	7.1 lbs / 3.2 kg

\* Product specifications, terms, and offerings are subject to change at any time without notice.

## Accessories

- Universal Projector Ceiling Mount (PRJ-MNT-UNIV)
- Motorized Electric Projector Screen: 130 in., 16:10 (SC-MOTW-130)
- Projector Lamp for the IN120x, IN120STx, and IN2120x Series (SP-LAMP-094)
- LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)
- LightCast Key (INA-LCKEY1)
- LightCast Key (Europe) (INA-LCKEY2)
- LightCast Key (Asia-Pacific) (INA-LCKEY3)
- Replacement Remote for Meeting Room Projectors (HW-NAVIGATOR-4)
- Presenter 4 RF Remote with Laser Pointer (HW-PRESENTER-4)
- Soft Carry Case for Value Projectors (CA-SOFTVAL-2)
- Projector Ceiling Mount System (Black) (PRJ-MNTKIT-UNIVB)
- Projector Ceiling Mount System (White) (PRJ-MNTKIT-UNIVW)
- VGA Cable (36 ft / 11 m) (SP-VGA-11M)
- Fixed Frame Projector Screen: 130 in., 16:10 (SC-FFW-130)
- Motorized Electric Projector Screen: 94 in., 16:10 (SC-MOTW-94)
- Fixed Frame Projector Screen: 94 in., 16:10 (SC-FFW-94)
- Manual Pull Up Projector Screen: 73 in., 16:9 (SC-PUW-73)
- Manual Pull Down Projector Screen: 92 in., 16:9 (SC-PDHD-92)
- Manual Pull Down Projector Screen: 106 in., 16:9 (SC-PDHD-106)
- DLP Link 3D Glasses by XPAND (X103-EDUX3-R1)
- SMART Mount Adapter (INA-SMRTADPT)
- 1 Year Extended Warranty for IN1XXX, IN2XXX, IN3XXX Projectors (EPW-PJM1)
- 2 Year Extended Warranty for IN1XXX, IN2XXX, IN3XXX Projectors (EPW-PJM2)