

## HDMI to VGA converter with audio - compact - 1920x1200

StarTech ID: HD2VGAMICRA



This HDMI® to VGA adapter lets you connect your HDMI computer to a VGA display or projector. The versatile adapter features a discrete 3.5mm audio output for extracting stereo audio from your HDMI signal, and supports PC resolutions up to 1920x1200.

### Versatile VGA compatibility

The adapter works with any HDMI equipped computer to add compatibility with VGA displays. Enabling VGA support on your Ultrabook™ or Chromebook™ means that you'll have the connection options you need to use almost any boardroom projector or display.

### Effortless setup and operation

The HDMI to VGA adapter doesn't require software or drivers, which saves you time and hassle when you need to make a quick connection. Plus, the adapter features a 3.5mm output which gives you the option to share the audio directly from your HDMI port.

### Compact for maximum portability

This compact HDMI to VGA adapter is lightweight and portable, and easily fits into any laptop carrying bag. The adapter has also been engineered with low-power architecture, so you won't need to carry a bulky external power adapter, or find access to an electrical outlet while you're on the go.

This converter will not output digitally encrypted content.

The HD2VGAMICRA is backed by a 2-year StarTech.com warranty and free lifetime technical support.

Notes: This converter is not compatible with Mac computers that use Intel HD 4000 cards (for example, Mac Mini). For specific support for these devices, StarTech.com offers the [HDMI to VGA Adapter](#)

[Converter](#) (MCHD2VGA).

### **Applications**

- Connect your Ultrabook or Chromebook to a boardroom display
- Use your VGA monitor as secondary display
- Carry the adapter with you while travelling to ensure your laptop is compatible with VGA displays in BYOD applications

### **Features**

- Increase the compatibility of your HDMI equipped Ultrabook or Chromebook by adding support for VGA
- Hassle-free setup, through plug-and-play installation
- Maximum portability with a small foot print and lightweight design
- Supports resolutions up to 1920x1200 (1080p)
- Discrete 3.5mm audio output

Technical Specifications

Warranty	2 Years
Adapter Style	Adapter
Audio	Yes
Chipset ID	CH7101A-BF QFN 40PIN SMD
Converter Type	Format Converter
Output Signal	VGA
Ports	1
Audio Specifications	2-channel stereo (3.5mm)
Maximum Digital Resolutions	1900x1200 @ 60Hz
Supported Resolutions	Widescreen(16/32 bit): 1920x1200, 1920x1080, 1680x1050, 1600x900, 1440x900, 1360x768, 1280x800, 1280x768, 1280x720  Standard(16/32 bit): 1600x1200, 1400x1050, 1280x1024, 1280x960, 1152x864, 1024x768, 800x600
Wide Screen Supported	Yes
Connector A	1 - HDMI (19 pin) Male Input
Connector B	1 - VGA (15 pin; High Density D-Sub) Female Output
Connector B	1 - 3.5 mm Mini-Jack (3 Position) Female Output
<b>Note</b>	This converter is not compatible with Mac computers that use Intel HD 4000 cards (Mac Mini), for specific support for these devices StarTech.com offers the [%product id="MCHD2VGA" text="Mac Mini to VGA adapter"%] (MCHD2VGA)  This converter will not output digitally encrypted content
Humidity	90% RH
Operating Temperature	10°C to 40°C (50°F to 104°F)
Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Shipping (Package)	0.8 oz [23 g]

Weight

Included in Package 1 - Compact HDMI to VGA adapter

Certifications, Reports and Compatibility

