



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model Number: B021-000-17

Rackmount Console - 1U Rackmount Console with 17" LCD



Highlights

- Control an entire network in just 1U of rack space; includes keyboard, 17" LCD screen, and touch pad
- Features a USB 2.0 pass-through port for connection of a USB peripheral, such as a flash drive, CAC card reader, etc.
- Connects to a PS/2 or USB server or KVM switch
- Supports video resolutions up to 1366 x 768
- Rackmountable in 19-inch system rack (1U), from 27" to 42" deep

Description

Tripp Lite's B021-000-17 1U Rackmount Console features an integrated 17" LCD panel, full 88-key keyboard, and touch pad, all in a 1U rackmountable housing. The included KVM cable kit allows for connection to a PS/2 computer or KVM, and a PS/2 to USB adapter is included, which can be used to connect to a USB computer or KVM. The unit features a USB 2.0 pass-through port for connection of a USB peripheral, such as a flash drive, CAC card reader, etc.. Your peripheral device connects to the USB type A port on the front of the unit, and your computer connects to the USB type A port on the back of the unit using a Tripp Lite [UR020-Series](#) type A M/M cable. Constructed of heavy-duty steel housing.

Applications

- Use where rack space is at a premium, and where a Server/KVM display is needed.

System Requirements

- Computer or KVM with a VGA monitor port and USB or PS/2 keyboard/mouse ports


Package Includes

- 1- B021-000-17 1U Rackmount Console
- 1- KVM Cable Kit (HD15M to HD15M + 2 PS/2 Male)
- 1-PS/2 to USB Adapter
- 1- C13 to 5-15P Power Cord
- 1- User Manual

Features

- Space savings with 1U 19-inch, rack-mount drawer design
- Features 17-inch LCD TFT active-matrix, color panel
- Features a USB pass-through port for connection of a USB peripheral, such as a flash drive, CAC card reader, etc.
- Supports resolutions of up to 1366 x 768
- Included PS/2 to USB adapter allows for connection to a USB computer or KVM
- Sleep mode when the monitor cover is closed
- Input 120/240 VAC
- Constructed of heavy-duty steel housing

Specifications

OVERVIEW	
PC/Server	VGA; USB; PS/2
INPUT	
Electrical Consumption	(Line Mode) 30W / (Standby Mode) 5W
UPC ASSIGNMENT	
Unit Carton UPC#	037332125279
PHYSICAL	
Color	Black
Style	1U Rack Console (non-KVM)
ENVIRONMENTAL	
BTUs	(Line Mode) 102 BTU/Hr / (Standby Mode) 17.06 BTU/Hr
CONNECTIONS	
Connector A	 HD15 (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

Related Items

Optional Products

Related Model	Description	Qty.
B004-008	KVM Switch - 8-Port 1U Rackmount KVM Switch	1
B019-000	KVM Switch Accessories - 2-Post Rackmount Bracket for B020,B021, B040, and B070 Consoles and KVM Consoles	1
B022-U16	KVM Switch - 16-Port NetDirector 1U Rackmount KVM Switch	1
UR020-003	Reversible USB 2.0 A-Male to A-Male Cable - 3ft	1
UR020-006	Universal Reversible USB 2.0 A-Male to A-Male Cable - 6ft	1
UR020-010	Universal Reversible USB 2.0 A-Male to A-Male Cable - 10ft	1
B072-016-IP2	16-Port, 2+1 User NetCommander Cat5 IP KVM Switch	1
B072-016-IP4	16-Port, 4+1 User NetCommander Cat5 IP KVM Switch	1
WEXT-KVM-A1	1-Year Warranty Extension - For select KVM Switches (see specific models for eligibility)	1
WEXT-KVM-A2	2-Year Warranty Extension - For select KVM Switches (see specific models for eligibility)	1
WEXT-KVM-A3	3-Year Warranty Extension - For select KVM Switches (see specific models for eligibility)	1
WEXT-KVM-A4	4-Year Warranty Extension - For select KVM Switches (see specific models for eligibility)	1
B072-032-IP2	32-Port, 2+1 User NetCommander Cat5 IP KVM Switch	1
B072-032-IP4	32-Port, 4+1 User NetCommander Cat5 IP KVM Switch	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at <http://www.tripplite.com/sku/B021-000-17>.

Copyright © 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.