

Product Highlights

You're Covered from Every Angle

Get ultra-wide coverage with a 180-degree wideangle lens and Infra-Red illumination that lets you watch over your home 24 hours a day

High-Quality Streams and Detection

1080P HD video ensures you capture the details you need, and sound and motion detection can trigger notifications right to your mobile device

Mobile App and Cloud-Enabled Device

Stay connected and get instant notifications via the mydlink™ Lite app and cloud service for peace of mind while you're on the go



DCS-2670L

Full HD 180-Degree Outdoor Wi-Fi Camera

Features

Camera

- High quality 1080P Full HD sensor provides detailed snapshots and crisp video
- 180-degree wide-angle lens for clear wholeroom coverage
- IP65 rating for waterproof durability
- Built-in IR LEDs to capture video in low-light environments, or even complete darkness

Security

- · Motion and sound level detection
- Send notifications and snapshots/video clips to your mobile device, or save them to a microSD
- Universal Plug and Play (uPnP) lets you access your device easily

Ease Of Use

- Connects to your wireless network so you can easily install the camera anywhere you have Wi-Fi access
- Backwards compatible with 802.11g/b devices

Remote Functionality

- View and manage your camera remotely using the handy mydlink Lite app or mydlink website
- DDNS support lets you conveniently connect to the camera for management when you're away

The DCS-2670L Full HD 180-Degree Outdoor Wi-Fi Camera boasts a horizon-wide 180° lens that easily captures your entire room in high-resolution 1080P. Its three-axis adjustment makes ceiling installations easy, and the built-in night vision, motion and sound detection, and handy mobile app empower you with knowing exactly what is happening anywhere, anytime.

Complete Coverage for Peace of Mind

Unlike most cameras on the market, the DCS-2670L features an ultra-wide view lens to give you a full 180° field of view, letting you cover an entire room with a single camera. Send notifications with snapshots or video clips whenever an event is detected and use the app or any web browser to remotely view live streams. Built-in motion detection keeps you aware of what's happening, and loud sounds picked up by the camera can trigger recording and send instant notifications. Night-time monitoring is possible with the built-in infrared LEDs which allow for night-time viewing of up to 10 meters (32.8 feet), so you can relax knowing you have round-the-clock monitoring of your home or small office.

Flexible Placement

When setting up a surveillance camera, you need to make sure that it can provide smooth video wherever you decide to install it. The DCS-2670L has onboard Wireless N to give you a longer range and higher bandwidth while still staying compatible with older wireless devices – for smoother HD video streams. The camera is also IP65-certified for waterproofness against the elements, so you can install it indoors or outdoors.

Access Anywhere with mydlink Cloud Service

Enhanced with mydlink support, the DCS-2670L makes it easier and more convenient for you to look after your family and check on your home or office. With a mydlink-enabled camera, you can stay up-to-date with notifications and check in on those you love at any time. Access your camera through the mydlink website or the mydlink Lite mobile app and you can view and manage your camera using your mobile phone, no matter where you are.



DCS-2670L Full HD 180-Degree Outdoor Wi-Fi Camera

Connections View Front View Light Sensor Reset Button microSD IR LEDs **Card Slot** 180° Camera Lens (behind cover) Status LED Microphone Camera Base Baseplate Power Ethernet Connector Connector

Camera		
 1/2.7" 2-Megapixel progressive CMOS sensor Minimum illumination: Color mode: 0.5 lux B/W mode (LEDs off): 0.1 lux B/W mode (LEDs on): 0 lux Minimum object distance 30 cm Lens focal length: 1.5 mm ± 3% 	 Aperture: F2.0 Angle of view (16:9): Horizontal: 180° Mounting angle: Vertical: 0° to 90° Horizontal: 0° to 180° 	
• IP65 compliant weatherproof housing ³		
Digital zoom Built-in microphone Configurable image size, quality, frame rate, and bit rate Wide Dynamic Range (WDR)	 Time stamp and text overlays Configurable motion detection windows Configurable brightness	
Simultaneous H.264 format compression H.264 multicast streaming	• JPEG for still images	
• 16:9 • 1920 x 1080, 1280 x 720, 800 x 448, 640 x 360 at up to 30 fps		
• AAC (32 kbps)	• G.711 (128 kbps)	
802.11n/g/b wireless with WPA/WPA2 encryption 10/100BASE-TX Fast Ethernet port Maximum data rate of 300 Mbps (PHY rate) ¹	microSD/SDHC/SDXC card slot, accepts cards up to 128 GB	
Prv6, IPv4, ARP, TCP, UDP, ICMP DHCP client NTP client (D-Link) DNS client DDNS client SMTP client SMTP client	HTTP server HTTPS (for configuration) uPnP port forwarding RTP/RTSP/RTCP Bonjour	
Administrator and user group protection Password authentication	HTTP and RTSP digest encryption	
	 Minimum illumination: Color mode: 0.5 lux B/W mode (LEDs off): 0.1 lux B/W mode (LEDs on): 0 lux Minimum object distance 30 cm Lens focal length: 1.5 mm ± 3% IP65 compliant weatherproof housing³ Digital zoom Built-in microphone Configurable image size, quality, frame rate, and bit rate Wide Dynamic Range (WDR) Simultaneous H.264 format compression H.264 multicast streaming 16:9 1920 x 1080, 1280 x 720, 800 x 448, 640 x 360 at up to 3 AAC (32 kbps) 802.11n/g/b wireless with WPA/WPA2 encryption 10/100BASE-TX Fast Ethernet port Maximum data rate of 300 Mbps (PHY rate)¹ IPv6, IPv4, ARP, TCP, UDP, ICMP DHCP client NTP client (D-Link) DNS client DDNS client DDNS client (D-Link) SMTP client Administrator and user group protection	



DCS-2670L Full HD 180-Degree Outdoor Wi-Fi Camera

System Integration		
System Requirements for mydlink Portal Web Management	The latest minimum system and browser requirements for mydlink website. ²	or using the mydlink portal can be found on your regional
Event Management	Motion detection Sound level detection Scheduled recording	Event notification and snapshot/video clip uploads to mobile device
Remote Management	Configuration interface accessible via a web browser	
Mobile Support	mydlink Lite mobile app for iPhone, iPad, iPod touch, and Android	
Physical		
Weight	• 360 grams (12.7 ounces) ± 5%	
Power Adapter	• Input: 100 to 240 V AC, 50/60 Hz	Output: 5 V DC 1.2 A
Power Consumption	• Maximum: 5 watts ± 5%	
Temperature	• Operating: -25 to 45 °C (-13 to 113 °F)	• Storage: -20 to 70 °C (-4 to 158 °F)
Humidity	Operating: 20% to 80% non-condensing	Storage: 5% to 95% non-condensing
Certifications	• CE • CE LVD • FCC	• ICES • RCM
Dimensions Diagram	ww 690 ww 690 o o o o o o o o o o o o o o o o o o o	102.1 mm

DCS-2670L Full HD 180-Degree Outdoor Wi-Fi Camera

Order Information		
Part Number	Description	
DCS-2670L	Full HD 180-Degree Outdoor Wi-Fi Camera	

Maximum wireless signal rate derived from IEEE standard 802.11 specifications. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials and construction, and network overhead, lower actual data throughput rate. Environmental factors will adversely affect wireless signal range.

Go to www.mydlink.com to see the latest supported OS and browser versions at Support > FAQ > mydlink Basic > System Requirement.

He65 standard: Effective against low-pressure water jets from all directions. It is recommended to place the device under a roof or shelter.

Updated 2017/07/06

