

Key Features

Laser Phosphor Technology | Full HD 1080p Resolution | Bright Images
in any Environment | Horizontal and Vertical Keystone Correction |
Reduced Input Latency



Product Description

With incredible Full HD resolution and a high brightness of 3,500 lumens, the ViewSonic® LS700HD laser projector delivers stunning home entertainment: day or night, in bright rooms or dark. Utilizing the latest laser light technology that lasts up to 20,000 hours, the LS700HD delivers long-term enjoyment for movies, games, and other multimedia entertainment. What's more, with high brightness, SuperColor™ technology, and room-filling sound, this projector provides an incredibly immersive home theater experience in nearly any room or environment. Set-up is a breeze too: 1.3x optical zoom and versatile connectivity options allow for more flexible mounting and easy installation. For an amazing home theater viewing experience with lifelike color and razor-sharp details, the LS700HD delivers.




01 Projection Lens
IR Remote Sensor
Focus/Zoom Rings
RS-232
Computer In

02 USB 5V/1.5A Out
LAN
Mini USB
AC In
Composite




03 Control Panel
04 HDMI (x2)
05 Audio In/Out
06 Monitor Out
07 Kensington® Lock Slot
08
09
10
11
12
13
14
15



1920 x 1080
RESOLUTION



3,500 ANSI
LUMENS



1.13~1.47
THROW RATIO

Contact Sales

-  call: 888.881.8781
-  email: salesinfo@viewsonic.com
-  visit: viewsonic.com

Display:

Type:	DLP Laser
Resolution Type:	HD (1920x1080)
Resolution:	1920 x 1080
Brightness (Lumens):	3,500 ANSI
Display Size (in.):	60 - 300 in. / 1.5 - 7.6 m
Throw Distance:	4.9 - 28.8 ft / 1.5 - 8.8 m
Throw Ratio:	1.13~1.47
Keystone:	Vertical ($\pm 40^\circ$) / Horizontal ($\pm 40^\circ$)
Lens:	1.3x Manual optical zoom / manual optical focus
Light Source Life, Normal (hours):	20000
Light Source Life, Dynamic Eco-Mode (hours):	20000
Color Depth:	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio:	3,000,000:1
Aspect Ratio:	16:9

Video Signal:

Frequency Horizontal:	15K~102KHz
Frequency Vertical:	23~120Hz

Compatibility:

PC Resolution (max):	1920 x 1080
Mac® Resolution (max):	1920 x 1080

Connector:

USB 2.0 Type A(1), Ethernet LAN (RJ45)(1), 3.5mm Audio Out(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI 1.4 (with HDCP 1.4)(2), VGA In(2), VGA Out(1), Composite RCA Video In(1), Mini USB(1)

Audio:

Internal Speakers:	2W (x1)
--------------------	---------

Power:

Voltage:	100-240V+/- 10%, 50/60Hz AC
Consumption (typical):	260W
Stand-by:	<0.5W

Controls:

Physical Controls:	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display:	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	0-90%

Additional Hardware:

Kensington Lock Slot:	1
-----------------------	---

Weight (imperial):

Net (lbs):	15.7
Gross (lbs):	20.1

Weight (metric):

Net (kg):	7.1
Gross (kg):	9.1

Dimensions (imperial) (WxHxD):

Packaging (in.):	19.7 x 6.2 x 15.8
Physical (in.):	15.6 x 6.2 x 12.4

Dimensions (metric) (WxHxD):

Packaging (mm):	500.4 x 157.5 x 401.3
Physical (mm):	396.0 x 157.0 x 314.0

General:

Regulations: FCC, cTUVus, ROHS

PACKAGE CONTENTS: LS700HD Projector, Power Cable, VGA Cable, Remote Control, Quick Start Guide

Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).

UPC: 766907981216

Accessories:

HB10B, IFP2710, PGD-350, PJ-SCW-1001W, PJ-WMK-006, PJ-WMK-007, VC10, VCB10